



## Product Safety Data Sheet

SDS #: 16-00647

2016-09-14

Revision 2

# DocuCentre SC2020

### Product Description / Product Identifier

Multifunction Equipment J-B230

### Speed (PPM)

20/20

### Mono / Color

Mono / Color

### ELECTRICAL INPUT INFORMATION

Voltage (Volts)	<b>220V-240V</b>
Rated Current (Amperes)	5
Frequency (Hertz)	50/60
Phase Connection	single

### POWER AND HEAT

	<b>Power (Watts)</b>	<b>Heat Output (BTU/Hr)</b>
Active <sup>1</sup>	1200	4095
Ready <sup>1</sup>	78	266
Sleep <sup>1</sup>	46	157
Sleep (2) <sup>1</sup>	1.4	5
Standby <sup>1</sup> (Off/FEMP) <sup>2</sup>	.04	0

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

Relative Humidity % 15-85% 10-32 °C

### PRODUCT SIZE

Depth	58.6 cm
Width	59.6 cm
Height	63.4 cm
Weight	48.5 kg

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE

LED

### CHEMICAL EMISSIONS

Chemical Emission Test Method RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 5.1 m<sup>3</sup> with 1 air change per hour.

### PARAMETER

### EMISSION RATE

TVOC	3.1 mg/h
Dust	0.37 mg/h
Ozone	0.52 mg/h
Styrene	0.036 mg/h
Benzene	0.003 mg/h

### ACOUSTICAL NOISE

	<b>Sound Power Level LwAd (B)</b>	<b>Sound Pressure Level Lpam (dBA)</b>
Standby	3.20	14.96
Run	7.03	54.04



## Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376  
Contact U.S. Only: [askxerox@xerox.com](mailto:askxerox@xerox.com)  
Contact Non-U.S. Only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)