

Safety Data Sheet

SDS #: A-0065BULK Dry Ink - Black

Issuing Date 1987-12-02 Revision Date 2015-04-21 Version 1

Active

1. Product and Company Identification

Trade Name Dry Ink for 5100, 5100 SE, 5800, 5885, 5890, 5895, 5900, 5900 I,

5990, 5995

Part no. 502S30917, 502S30918, 502S30919, 502S30920

Color Black
Pure substance/preparation Preparation

Identified uses Xerographic printing

Manufactured by Xerox Corporation

Rochester, NY 14644

Emergency telephone Safety Information US: (800) 275-9376

Chemical Emergency only (Chemtrec) (800) 424-9300

Hazards Identification

Warning

Emergency Overview

May form combustible dust concentrations in air

ColorAppearancePhysical stateOdorBlackPowderSolidFaint

Classification of the substance or mixture

Industrial use / Bulk containers

OSHA Hazard Classification Combustible dust

Label elements

Signal Word Warning

Hazard Statements May cause combustible dust concentrations in air

Precautionary Statements Prevent dust cloud

Sweep up or vacuum with electrically protected vacuum cleaner and collect in suitable

container for disposal.

Use non-sparking tools and equipment

Avoid ignition sources.

Potential Health Effects



SDS #: A-0065BULK Dry Ink - Black Page 2/7

Principle Routes of Exposure

Acute toxicity

Inhalation

EyesNo known effectSkinNo known effectInhalationNo known effectIngestionNo known effect

Chronic effects

Main symptoms Overexposure may cause:

mild respiratory irritation similar to nuisance dust.

Aggravated medical conditions

itions None under normal use conditions

Environmental hazard

The environmental impact of this product has not been fully investigated. However, this preparation is not expected to present significant adverse environmental effects.

3. Composition/Information on Ingredients

Chemical Name	CAS-No	Weight %
Styrene/butadiene copolymer	9003-55-8	60-65
Acrylic resin	9017-48-5	20-25
Carbon Black	1333-86-4	5-10
Polypropylene wax	9003-07-0	1-6

4. First Aid Measures

General advice For external use only. When symptoms persist or in all cases of doubt seek medical advice.

Show this material safety data sheet to the doctor in attendance.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes

Skin contact Wash skin with soap and water

Inhalation Move to fresh air

Ingestion Rinse mouth with water and afterwards drink plenty of water or milk

Notes to physician Treat symptomatically

Protection of first-aiders No special protective equipment required

Fire-Fighting Measures

Flammable properties Not flammable. Will not readily ignite

Flash point Not applicable

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire

Specific hazards arising from the chemical

Fine dust dispersed in air, in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard

Hazardous combustion products

Hazardous decomposition products due to incomplete

combustion Carbon oxides

Nitrogen oxides (NOx)



SDS #: A-0065BULK Dry Ink - Black Page 3/7

•

Explosion Data

Sensitivity to Mechanical Impact Not impact sensitive

Sensitivity to Static Discharge Fine dust dispersed in air, in sufficient concentrations, and in the

presence of an ignition source is a potential dust explosion

hazard

Note See Section 9 for physical properties related to explosibility

Protective Equipment and Precautions for Firefighters

In the event of fire and/or explosion do not breathe fumes. Wear fire/flame resistant/retardant clothing. Use self-contained pressure-demand breathing apparatus if needed to prevent exposure to smoke or airborne toxins.

6. Accidental Release Measures

Personal Precautions Avoid breathing dust

Environmental Precautions No special environmental precautions required

Methods for containment Prevent dust cloud

Methods for cleaning up Prevent dust cloud. Sweep up or vacuum up spillage and collect in suitable container for

disposal. Use non-sparking tools and equipment. Avoid ignition sources.

Other Information The environmental impact of this product has not been fully investigated. However, this

preparation is not expected to present significant adverse environmental effects.

7. Handling and Storage

Advice on safe handling Handling practices and processes should be consistent with the safe handling of

combustible dust.
Prevent dust cloud

In case of insufficient ventilation, wear suitable respiratory equipment Keep away from open flames, hot surfaces and sources of ignition

Take precautionary measures against static discharges

Technical measures/Storage

conditions

Keep container tightly closed in a dry and well-ventilated place

Store at room temperature

Hygiene measures Handle in accordance with good industrial hygiene and safety practice

Industrial User Do not eat, drink or smoke when using this product.

Wash hands before breaks and at the end of workday

Provide regular cleaning of equipment, work area and clothing.

8. Exposure Controls/Personal Protection

Exposure guidelines

Product information

ACGIH TLV TWA

ACGIH TLV TWA

OSHA PEL TWA

OSHA PEL TWA

OSHA PEL TWA

OSHA PEL TWA

Serox Exposure Limit

Xerox Exposure Limit

ACGIH TLV TWA

10 mg/m³ (inhalable particles)

3 mg/m³ (respirable dust)

5 mg/m³ (respirable dust)

2.5 mg/m³ (total dust)

0.4 mg/m³ (respirable dust)



SDS #: A-0065BULK Dry Ink - Black Page 4/7

Other Information

The results obtained from a Xerox sponsored Chronic Toner Inhalation Study demonstrated no lung changes in rats for the lowest (1 mg/m³) exposure level (the level most relevant to potential human exposure). A very slight degree of fibrosis was noted in 25% of animals at the middle (4mg/m³) exposure level, while a slight degree of fibrosis was noted in all the animals at the highest (16 mg/m³) exposure level. These findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged period. This study was conducted using a special test toner to comply with an EPA testing protocol.

Occupational Exposure Controls

Engineering measures Engineering controls should be used to maintain airborne dust levels below established

exposure limits

Industrial use Equipment and processes should be designed and operated in accordance with directives

for safe handling of combustible dust. Provide appropriate exhaust ventilation at places where dust is formed. Ensure all equipment is electrically grounded before beginning

transfer operations.

Personal Protective Equipment

Industrial use / Bulk containers

Eye/Face protection No special protective equipment required

Skin and body protection
No special protective equipment required

Hand protection No special protective equipment required

Industrial use If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn Wear protective eyewear (goggles)

9. Physical and Chemical Properties

AppearancePowderOdorFaintOdor thresholdNot applicablePhysical stateSolidpHNot applicableColorBlack

Flash point Not applicable Boiling Not applicable

point/range

Softening point 49 - 60 °C / 120 - 140 °F Autoignition Not applicable

temperature

Flammability Limits in Air Not applicable

Explosive properties (Method: ASTM E 1226 Standard Test Method for Explosibility of Dust Clouds)

Maximum rate of explosion pressure rise (KSt) 185 - 278 m*bars/sec

Maximum explosion pressure (Pmax) 7.9 - 9.0 bar

Minimum ignition energy <3 millijoules

Vapor pressureNot applicableVapor densityNot applicableWater solubilityNegligibleViscosityNot applicablePartition coefficientNot applicableEvaporation rateNot applicable



SDS #: A-0065BULK Dry Ink - Black Page 5/7

•

Melting point/rangeNot determinedFreezing pointNot applicableDecomposition temperatureNot determined

Specific gravity ~

10. Stability and Reactivity

Reactivity No dangerous reaction known under conditions of normal use

Stability Stable under normal conditions

Incompatible products None

Conditions to Avoid Heat, flames and sparks

Take precautionary measures against static discharges

Prevent dust cloud

Hazardous Decomposition Products None under normal use

Hazardous polymerization Hazardous polymerization does not occur

Hazardous reactions None under normal processing

11. Toxicological Information

The toxicity data noted below is based on the test results of similar reprographic materials.

Acute toxicity

Product information

Irritation No skin irritation, No eye irritation

 LD50 Oral
 > 5 g/kg (rat)

 LD50 Dermal
 > 5 g/kg (rabbit)

 LC50 Inhalation:
 > 5 mg/L (rat, 4 hr)

EyesNo known effectSkinNo known effectInhalationNo known effectIngestionNo known effect

Chronic toxicity

Product information

Chronic effects No known effects under normal use conditions

Main symptoms Overexposure may cause: mild respiratory irritation similar to nuisance dust.

Aggravated medical conditions
Carcinogenicity

None under normal use conditions
See "Other Information" in this section.

Chemical Name	IARC	NTP
Carbon Black	2B	

Other information

The IARC (International Agency for Research on Cancer) has listed carbon black as "possibly carcinogenic to humans". The classification is based on studies evaluating pure, "free" carbon black. In contrast, toner is a formulation composed of specially prepared polymer and a small amount of carbon black (or other pigment). In the process of making toner, the small amount of carbon black becomes encapsulated within a matrix. Xerox has performed extensive testing of toner, including a chronic bioassay (test for potential carcinogenicity). Exposure to toner did not produce evidence of cancer in exposed animals. The results were submitted to regulatory agencies and published extensively.

Other toxic effects

Product information



SDS #: A-0065BULK Page 6/7 Dry Ink - Black

Sensitization No sensitization responses were observed

Mutagenic effects Not mutagenic in AMES Test

Developmental toxicity None known. **Teratogenicity** None known Target organ effects None known

Other adverse effects None known **Aspiration Hazard** Not applicable

12. Ecological Information

Ecotoxicity

The environmental impact of this product has not been fully investigated. However, this preparation is not expected to present significant adverse environmental effects.

No information available. Persistence and degradability

13. Disposal Considerations

Waste Disposal Methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated packaging Dispose of in accordance with local regulations.

14. Transport Information

This material is not subject to regulation as a hazardous material for shipping. Note

15. Regulatory Information

International Inventories

Complies **TSCA DSL/NDSL** Complies **EINECS/ELINCS** Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations. Part 372. **Clean Water Act**

This product is not regulated as a pollutant pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product is not regulated as a hazardous air pollutant (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.



SDS #: A-0065BULK Dry Ink - Black Page 7/7

TSCA

TSCA 12(b) does not apply to this product.

U.S. State Regulations

California Proposition 65

Carbon black is regulated under California Proposition 65 only if in the form of "airborne, unbound particles of respirable size". Toner products do not contain carbon black in the form of "airborne, unbound particles of respirable size". Therefore, the requirements of Proposition 65 do not apply to this product.

Chemical Name	CAS-No	California Prop. 65
Carbon Black	1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Although this product contains substances included in some U.S. State Right-to-Know regulations, the particles are bound in a unique matrix and, therefore, the product does not pose any specific hazard.

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. Other Information

Issuing Date 1987-12-02

Revision Date 2015-04-21

Revision Note Updated for OSHA HazCom 2012 and WHMIS 2015

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

end