

Product Safety Data Sheet

SDS #: 14-00625

2014-10-09 Revision 1

ColorQube 8580N ColorQube 8580DN ColorQube 8880

Product Description Colour Solid Ink Printer

Speed (PPM) 51 Mono / Color Colour

ELECTRICAL INPUT INFORMATION

| Voltage (Volts) | 110V-127V | 220V-240V |
|--------------------------|-----------|-----------|
| Rated Current (Amperes): | 12-6 | 12-6 |
| Frequency (Hertz) | 50/60 | 50/60 |
| Phase Connection | single | sinale |

POWER AND HEAT

| | Power (Watts) | Heat Output (BTU/Hr) | Power (Watts) | Heat Output (BTU/Hr) |
|--|------------------|-------------------------|------------------|-------------------------|
| Active ¹ | 249.6 | 860 | 282.9 | 829.3 |
| Ready ¹ | 68 | 355 | 76 | 365.2 |
| Sleep ¹ | 53 | 245.7 | 69 | 256 |
| Sleep 2 ¹ | 36 | 153.6 | 38 | 160.4 |
| Standby ¹ (Off/FEMP) ² | 0.3 | 1.2 | 0.9 | 3.6 |

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity % 10-80%

Ambient Temperature 50-90 °F / 10-32 °C

PRODUCT SIZE

| Depth | 26.5 in. | 67.3 cm |
|--------|----------|---------|
| Width | 22 in. | 55.9 cm |
| Height | 21.3 in. | 54.0 cm |
| Weight | 75 lbs. | 34 kg |

For additional information regarding different configurations please contact your local sales representative.

CHEMICAL EMISSIONS

Chemical Emission Test Methodology RAL - UZ122

The machine was tested under the conditions as specified in the standard inside a room of 6 m³ with 1 air changes per hour.

| PARAMETER | Concentration | Emission Rate |
|---|---------------|---------------|
| Total Volatile Organic Compounds (TVOC) | 138 μg/m³ | 7.9 mg/h |
| Dust | 12.8 μg/m³ | 2.0 mg/h |
| Ozone | <10 µg/m³ | <0.3 mg/h |
| Styrene | 3.3 µg/m³ | 0.21 mg/h |
| Benzene | <0.5 μg/m³ | <0.03 mg/h |

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

| | Sound Power Level LwAd (B) | Sound Pressure Level Lpam (dBA) |
|------------------|-------------------------------|------------------------------------|
| Standby | 3.0 | <20 |
| Run - continuous | 7.3 | 58 |

² FEMP - Federal Energy Management Program



Product Safety Data Sheet

SUPPLIES

MSDS Number(s) [Europe only] 3-5004

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issaunce of this Product Safety Data Sheet, Xerox does not asume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Contact U.S. Only: usa.xerox.EHS@xerox.com Contact Non-U.S. Only: ehs-europe@xerox.com