

Product: 4517/4517MP/DocuPrint N17

PSDS No.: 0753
ISSUE DATE: 01/09/96
REV. DATE: 01/11/01

Section I - Product Identification

Manufacturer's Name

Fuji Xerox Co. Ltd.

Manufacturer's Address

2274 Hongo, Ebina-shi

Product Designation

4517/4517MP/DocuPrint N17

Emergency No. EH&S Inquiries
 (585) 422-2177 (800) 828-6571

Product Identifier

4UM

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)	Branch Cir. Protection (Amps)
100 – 120	6.2	60 / 50	15

Line Cord/Plug Specification
 Equipped with Appliance Coupler
 Supplied with Detachable Cord
 NEMA Type 5-15P

Power Consumption (Watts)*
 Running: 350

Agency Approval
UL1950 File Number E158002
CSA950 File Number LR104813

Section III - Supplies

Toner	Xerox Part No. 113R00095	Material Safety Data Sheet Article ** (A6)
-------	------------------------------------	--

Section IV - Environmental Information

Product Size Configuration: (Centimeters)	Heat Emission* (BTU/HR)	Environmental Limitations
D: 418 W: 442 H: 294	Running: 1,095	<u>Min</u> <u>Max</u> Relative Humidity (%) 15 85 Ambient Temp. (°C) 10 32

Floor Space Requirements
 (Meters / Feet)
 N/A - Desktop Product

Weight
 (K Grams / Lbs.)
 18.6 / 41

* Based on a five-minute average

** MSDS is not required by OSHA Hazard Communication Std., 29CFR or WHMIS HPA (Section II (2))

Section V - Emission/Exposure Information*

Light Source

Semiconductor Laser Diode

FDA registered Class 1 Laser System.

There is no operator or service access to the beam.

FDA Accession #

9220485-23

Electromagnetic Emissions

US FCC: Class B

Canada IC: Class B

Audible Noise

Run 49.5 dB(A)

Standby 35.0 dB(A)

TLV**

85.0 dB(A)

Emissions

Ozone

<10 ug/min

0 ppm (TWA)

TLV

0.1ppm

Concentration Based on Simulation Model:

Daily Copy Volume 1,920 copies / 8 hours

Room Size 27.6 m³

1/2 Air Room Change per Hour

Total Dust

0.0039 mg/m³

TLV

0.1 mg/m³

* Based on a five minute average

** **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.