



Product Safety Data Sheet

SDS # : 13-00588
2016-01-22
Revision 4

WorkCentre 7855 WorkCentre 7855i

Product Description / Product Identifier

Multi-Function Equipment / J-B130

Speed (PPM)

55 / 50

Mono / Color

Mono / Color

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)		
Rated Current (Amperes):	12	10
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	828	2823	862	2939
Ready ¹	85.7	292	121	413
Sleep ¹	80.0	274	94.6	323
Sleep 2 ¹	4.3	14	4.8	16
Standby ¹ (Off/FEMP) ²	.07	.2	.3	1

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	20-80%	
Ambient Temperature	50-90 °F	/ 10-32 °C

PRODUCT SIZE

Depth	27.5 in.	69.9 cm
Width	41.9 in.	106.4 cm
Height	45.2 in.	114.9 cm
Weight	308 lbs	140 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

LED

CHEMICAL EMISSIONS

Chemical Emission Test Methodology RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 5 m³ with 1 air change per hour.

PARAMETER	Monochrome Emission Rate	Colour Emission Rate
Total Volatile Organic Compounds (TVOC)	3.8 mg/h	7.5 mg/h
Dust	None detected	None detected
Ozone	0.24 mg/h	0.40 mg/h
Styrene	0.074 mg/h	0.077 mg/h
Benzene	0.017 mg/h	0.020 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level LpAd (dBA)
Standby	3.6	18.5
Run - continuous	6.8	55.8



Product Safety Data Sheet

SUPPLIES

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Contact U.S. Only: usa.xerox.EHS@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com