



PRODUCT DESCRIPTION

WorkCentre 5020 Multifunction copier

	Standard	Certifying Body	Report Reference/ Licence
<u>ELECTRICAL & MECHANICAL CERTIFICATION</u>	IEC60950-1 : 2005	CQC	CN9594
	EN60950—1:2006+A11:2009	CQC	2010.12.14

	Standard	Certifying Body	Report Reference/ Licence
<u>ELECTRO-MAGNETIC COMPATIBILITY</u>	2004/108/EC	SIMT Fuji Xerox	200710-3-07029E EPS-EMCRPT-2006-074

<u>HEAT OUTPUT</u>			
Plug in, Off Mode BTU/hr	Sleep Mode BTU/hr	Low Power BTU/hr	Running (Average) BTU/hr
0	18	321	3960

<u>POWER</u>			
Plug in, Off Mode Watts	Sleep Mode Watts	Low Power Watts	Running (Average) Watts
0	6	107	1320

Note:
 The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

ENVIRONMENTAL LIMITATIONS

Relative Humidity (%): 15 – 85	Ambient Temperature (°C): 10 -32
-----------------------------------	-------------------------------------

LIGHT SOURCE

Class 1 Laser Product containing an embedded Class 3B Laser

AUDIBLE NOISE

Operating Conditions	Sound Pressure LpAd (dB) Operator Position	Sound Power LwAd (B)
Standby	28	4.2
Continuous	58	6.7

Number: 2-0460
Issue No: 2 (AO 4297)
Date: Jan 2011
Page: 2 of 2

Product Safety Data Sheet WorkCentre 5020



CHEMICAL EMISSIONS

	Concentration mg/m ³
Total dust, including toner	0.035
Ozone	0.01
Total Volatile Organic Compounds	0.5

OZONE FILTER REPLACEMENT

Not Applicable

PRODUCT DIMENSIONS

Depth	532 mm	Width	595 mm	Height	528 mm
-------	--------	-------	--------	--------	--------

SPACE REQUIREMENTS

Not applicable – Desktop equipment

WEIGHT

32 kg