



Product Safety Data Sheet

SDS # : 18-00680

2018-01-18

Revision 1

Xerox® AltaLink® C8030 Color Multifunction Printer

Product Description / Product Identifier

Multifunction Equipment

J-A330

J-B330

Speed (PPM)

30

Mono / Color

Color

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)		
Rated Current (Amperes)	12/16	8/10
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	652.6	2225.4	666.8	2273.8
Ready ¹	63.0	214.8	61.5	209.7
Sleep ¹	60.0	204.6	57.7	196.7
Sleep (2) ¹	3.53	12.0	3.84	13.1
Standby ¹ (Off/FEMP) ²	0.072	0.245	0.324	1.10

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	15-85%
Ambient Temperature	50-90 °F / 10-32 °C

PRODUCT SIZE

Depth	28.9 in.	73.4 cm
Width	43.6 in.	110.7 cm
Height	45.2 in.	114.8 cm
Weight	275.5 lbs	125 kg

SPACE REQUIREMENTS

Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

LED

CHEMICAL EMISSIONS

Chemical Emission Test Method RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 57.5 m³ with 2 air changes per hour.

PARAMETER

PARAMETER	Color Emission Rate	Monochrome Emission Rate
TVOC	3.0 mg/h	1.4 mg/h
Dust	0.140 mg/h	0.194 mg/h
Ozone	0.170 mg/h	0.132 mg/h
Styrene	0.041 mg/h	0.028 mg/h
Benzene	0.014 mg/h	0.009 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level LpAd (dBA)
Standby	3.39	15.3
Run	6.40	47.2



Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com