

Safety Data Sheet

SDS # : P-7018BULK	Replenisher - Blac and Y	k, Cyan, Magenta ellow	
Issuing Date 2015-03-23	Revision Date 2	015-10-21	Version 1
			Active
1. Product and Company Id	entification		
Trade Name Replenishe	er for DocuColo	r 8080	
Part no. 502S68804			
Color Pure substance/preparation	Black, Cyan, Magenta, Yel Preparation	low	
Identified uses	Xerographic printing		
Manufactured by	Xerox Corporation Rochester, NY 14644		
Emergency telephone	Safety Information US: (80 Chemical Emergency only	0) 275-9376 (Chemtrec) (800) 424-9300	
2. Hazards Identification			
Warning Emergency Overview May form combustible dust concentrations in air			
Color Black, Cyan, Magenta, Yellow	Appearance Powder	Physical state Solid	Odor Faint
Classification of the subst	ance or mixture		
Industrial use / Bulk contain	ers		
OSHA Hazard Classification	Combustible dust		
Label elements			
Signal Word	Warning		
Hazard Statements	May cause combustible du	st concentrations in air	
Precautionary Statements	Prevent dust cloud Sweep up or vacuum with container for disposal. Use non-sparking tools and Keep away from sources of	electrically protected vacuum clean d equipment f ignition - No smoking	er and collect in suitable

Potential Health Effects



Page 2/7

SDS # : P-7018BULK

Replenisher - Black, Cyan, Magenta and Yellow

Principle Routes of Exposure Acute toxicity	Inhalation
Eyes	No known effect
Skin	No known effect
Inhalation	No known effect
Ingestion	No known effect
Chronic effects	
Main symptoms	Overexposure may cause:
	mild respiratory irritation similar to nuisance dust.
Aggravated medical conditions	None under normal use conditions
Environmental hazard	The environmental impact of this product has not been fully investigated. However, this preparation is not expected to present significant adverse environmental effects.

3. Composition/Information on Ingredients

Product Description

This formulation represents multiple colors and the component list includes multiple pigments. The actual toner formulation for each color will differ only in the pigment used.

Chemical Name	CAS-No	Weight %
Polyester resin	122970-65-4	40-70
Polyester resin	39392-25-7	10-35
Ferrite	66402-68-4	10-30
Yellow pigment	4531-49-1	0-10
Cyan Pigment	147-14-8	0-10
Carbon Black	1333-86-4	0-10
Magenta Pigment	980-26-7	0-10
Titanium dioxide	13463-67-7	<1

4. First Aid Measures

General advice	For external use only. When symptoms persist or in all cases of doubt seek medical advice. Show this material safety data sheet to the doctor in attendance.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes
Skin contact	Wash skin with soap and water
Inhalation	Move to fresh air
Ingestion	Rinse mouth with water and afterwards drink plenty of water or milk
Notes to physician	Treat symptomatically
Protection of first-aiders	No special protective equipment required

5. Fire-Fighting Measures

Flammable properties	Not flammable. Will not readily ignite
Flash point	Not applicable
Suitable extinguishing media	Use water spray or fog; do not use straight streams, Foam
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire



Replenisher - Black, Cyan, Magenta and Yellow

Page 3/7

<u>Specific hazards arising from the chemical</u> Fine dust dispersed in air, in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard

Hazardous combustion products	Hazardous decomposition products due to incomplete combustion, Carbon oxides, Nitrogen oxides (NOx)
Explosion Data	
Sensitivity to Mechanical Impact	Not impact sensitive
Sensitivity to Static Discharge	Fine dust dispersed in air, in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard
NUM	

Note

See Section 9 for physical properties related to explosibility

Protective Equipment and Precautions for Firefighters

In the event of fire and/or explosion do not breathe fumes. Wear fire/flame resistant/retardant clothing. Use self-contained pressure-demand breathing apparatus if needed to prevent exposure to smoke or airborne toxins.

6. Accidental Release Me	asures
Personal Precautions	Avoid breathing dust
Environmental Precautions	No special environmental precautions required
Methods for containment	Prevent dust cloud
Methods for cleaning up	Prevent dust cloud. Sweep up or vacuum up spillage and collect in suitable container for disposal. Use non-sparking tools and equipment. Avoid ignition sources.
Other information	The environmental impact of this product has not been fully investigated. However, this preparation is not expected to present significant adverse environmental effects.
7. Handling and Storage	
Advice on safe handling	Handling practices and processes should be consistent with the safe handling of combustible dust. Prevent dust cloud In case of insufficient ventilation, wear suitable respiratory equipment Keep away from open flames, hot surfaces and sources of ignition Take precautionary measures against static discharges
Technical measures/Storage conditions	Keep container tightly closed in a dry and well-ventilated place, Store at room temperature
Hygiene measures	Handle in accordance with good industrial hygiene and safety practice
Industrial User	Do not eat, drink or smoke when using this product Wash hands before breaks and at the end of workday Provide regular cleaning of equipment, work area and clothing.

8. Exposure Controls/Personal Protection

```
Exposure guidelines
Product information
```

No information available



Page 4/7

SDS #: P-7018BULK

Replenisher - Black, Cyan, Magenta and Yellow

ACGIH TLV TWA	10 mg/m ³ (inhalable particles)
ACGIH TLV TWA	3 mg/m ³ (respirable dust)
OSHA PEL TWA	15 mg/m ³ (total dust)
OSHA PEL TWA	5 mg/m ³ (respirable dust)
Xerox Exposure Limit	2.5 mg/m ³ (total dust)
Xerox Exposure Limit	0.4 mg/m ³ (respirable dust)

Other information

The results obtained from a Xerox sponsored Chronic Toner Inhalation Study demonstrated no lung changes in rats for the lowest (1 mg/m³) exposure level (the level most relevant to potential human exposure). A very slight degree of fibrosis was noted in 25% of animals at the middle (4mg/m³) exposure level, while a slight degree of fibrosis was noted in all the animals at the highest (16 mg/m³) exposure level. These findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for a prolonged period. This study was conducted using a special test toner to comply with an EPA testing protocol.

Occupational Exposure Controls

Engineering measures	Engineering controls should be used to maintain airborne dust levels below established exposure limits
Industrial use	Equipment and processes should be designed and operated in accordance with directives for safe handling of combustible dust. Provide appropriate exhaust ventilation at places where dust is formed. Ensure all equipment is electrically grounded before beginning transfer operations.

Personal Protective Equipment

Industrial use / Bulk containers

Respiratory protection	No special protective equipment required
Eye/Face protection	No special protective equipment required
Skin and body protection	No special protective equipment required
Hand protection	No special protective equipment required
Industrial use	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn Wear protective eyewear (goggles)

9. Physical and Chemical Properties

Appearance Odor threshold pH Flash point Autoignition temperature	Powder Not applicable Not applicable Not applicable Not applicable		Odor Physical state Color Boiling point/range	Faint Solid Black, Cyan, Magenta, Yellow Not applicable
Flammability Lim	nits in Air	Not applicable		
Explosive proper	rties		26 Standard Test Me	thod for Explosibility of Dust Clouds)



Page 5/7

Replenisher - Black, Cyan, Magenta and Yellow

7.9 - 9.0 bar

SDS # : P-7018BULK

Maximum explosion pressure (Pmax)

Minimum ignition energy Vapor pressure Vapor density Water solubility Viscosity Partition coefficient Evaporation rate Melting point/range Freezing point Decomposition temperature Specific gravity	<3 millijoules Not applicable Not applicable Not applicable Not applicable Not applicable Not determined Not determined Not determined ~ 1 (toner component)
10. Stability and Reactivity	/
Reactivity	No dangerous reaction known under conditions of normal use
Stability	Stable under normal conditions
Incompatible products	None
Conditions to Avoid	Heat, flames and sparks, Take precautionary measures against static discharges, Prevent dust cloud
Hazardous Decomposition Produc	ts None under normal use
Hazardous polymerization	Hazardous polymerization does not occur

11. Toxicological Information

The toxicity data noted below is based on the test results of similar reprographic materials.

None under normal processing

Acute toxicity

Hazardous reactions

Product information					
Irritation	No skin irritation, No eye irritation > 5 g/kg (rat) > 5 g/kg (rabbit)				
LD50 Oral					
LD50 Dermal					
LC50 Inhalation	> 5 mg/L (rat, 4 hr)				
Eyes	No known	effect			
Skin	No known	effect			
Inhalation	No known effect No known effect				
Ingestion					
Chronic toxicity					
Product information					
Chronic effects	No known	effects under normal use conditions			
Main symptoms	Overexposure may cause: mild respiratory irritation similar to nuisance dust.				
Aggravated medical conditions	None und	er normal use conditions			
Carcinogenicity		r Information" in this section.			
Chemical Name		IARC	NTP		
Carbon Black		2B			
Titanium dioxide		2B			

BR547



Replenisher - Black, Cyan, Magenta and Yellow

Other information

The IARC (International Agency for Research on Cancer) has listed carbon black as "possibly carcinogenic to humans". The classification is based on studies evaluating pure, "free" carbon black. In contrast, toner is a formulation composed of specially prepared polymer and a small amount of carbon black (or other pigment). In the process of making toner, the small amount of carbon black becomes encapsulated within a matrix. Xerox has performed extensive testing of toner, including a chronic bioassay (test for potential carcinogenicity). Exposure to toner did not produce evidence of cancer in exposed animals. The results were submitted to regulatory agencies and published extensively.

The IARC (International Agency for Research on Cancer) has listed titanium dioxide as "possibly carcinogenic to humans". The classification is based on studies in rats using pure, unbound TiO2. Based on the review of available study results, when this product is used as intended, Xerox has concluded that the presence of titanium dioxide in this mixture does not present an increased risk of lung cancer or chronic respiratory disease.

Other toxic effects					
Product information					
Sensitization	No sensitization responses were observed				
Mutagenic effects	Not mutagenic in AMES Test				
Developmental toxicity	None known				
Teratogenicity	None known				
Target organ effects	None known				
Other adverse effects Aspiration Hazard	None known Not applicable				

12. Ecological Information

Ecotoxicity

The environmental impact of this product has not been fully investigated. However, this preparation is not expected to present significant adverse environmental effects.

Persistence and degradability No information available.

13. Disposal Consideration	S
Waste Disposal Methods	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated packaging	Dispose of in accordance with local regulations.
14. Transport Information	
Note	This material is not subject to regulation as a hazardous material for shipping

15. Regulatory Information

International Inventories

Page 6/7



Page 7/7

SDS #: P-7018BULK

Replenisher - Black, Cyan, Magenta and Yellow

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372 **Clean Water Act**

This product is not regulated as a pollutant pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product is not regulated as a hazardous air pollutant (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

TSCA

TSCA 12(b) does not apply to this product.

U.S. State Regulations

California Proposition 65

Carbon black is regulated under California Proposition 65 only if in the form of "airborne, unbound particles of respirable size". Toner products do not contain carbon black in the form of "airborne, unbound particles of respirable size". Therefore, the requirements of Proposition 65 do not apply to this product.

Titanium dioxide is regulated under California Proposition 65 only if a product results in exposure in the form of "airborne, unbound particles of respirable size". Toner products do not result in exposure to titanium dioxide in the form of "airborne, unbound particles of respirable size". Therefore, the requirements of Proposition 65 do not apply to this product.

Chemical Name	CAS-No	California Prop. 65
Carbon Black	1333-86-4	Carcinogen
Titanium dioxide	13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Although this product contains substances included in some U.S. State Right-to-Know regulations, the particles are bound in a unique matrix and, therefore, the product does not pose any specific hazard.

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

16. Other Information		
Issuing Date	2015-03-23	
Revision Date	2015-10-21	
Revision Note	(M)SDS sections updated:, 3	

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.