



## Product Safety Data Sheet

SDS #: 16-00644

2016-09-08

Revision 1

# WorkCentre 3335

### Product Description

Speed (PPM)

Mono / Color

Multifunction Equipment

35

Monochrome

### ELECTRICAL INPUT INFORMATION

Voltage (Volts)

110V-127V

220V-240V

Rated Current (Amperes)

6.5

3.5

Frequency (Hertz)

50/60

50/60

Phase Connection

single

single

### POWER AND HEAT

|  | Power<br>(Watts) | Heat Output<br>(BTU/Hr) | Power<br>(Watts) | Heat Output<br>(BTU/Hr) |
|--|------------------|-------------------------|------------------|-------------------------|
| Active <sup>1</sup>                          | 624.7            | 2131.6                  | 647.5            | 2209.4                  |
| Ready <sup>1</sup>                           | 47.5             | 162.1                   | 48.2             | 164.5                   |
| Sleep <sup>1</sup>                           | 2.0              | 6.8                     | 2.2              | 7.5                     |
| Standby <sup>1</sup> (Off/FEMP) <sup>2</sup> | 0.0              | 0.0                     | 0.0              | 0.0                     |

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

Relative Humidity %

10-85%

Ambient Temperature

50-90 °F / 10-32 °C

### PRODUCT SIZE

|        |           |          |
|--------|-----------|----------|
| Depth  | 16.6 in.  | 42.1 cm  |
| Width  | 16.3 in.  | 41.5 cm  |
| Height | 17.7 in.  | 44.9 cm  |
| Weight | 34.26 lbs | 15.54 kg |

### SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE

Class 1 Laser product containing an embedded Class 3B Laser

### CHEMICAL EMISSIONS

Chemical Emission Test Method

RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 5 m<sup>3</sup> with 1 air changes per hour.

### PARAMETER

#### EMISSION RATE

|       |           |
|-------|-----------|
| TVOC  | 1.67 mg/h |
| Dust  | 0.40 mg/h |
| Ozone | 0.30 mg/h |

### ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

|         | Sound Power Level<br>LwAd (B) | Sound Pressure Level<br>Lpam (dBA) |
|---------|-------------------------------|------------------------------------|
| Standby | -                             | <32                                |
| Run     | 6.78                          | 53.3                               |



## Product Safety Data Sheet

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Inquiries U.S. Only: 1-800-275-9376  
Contact U.S. Only: [askxerox@xerox.com](mailto:askxerox@xerox.com)  
Contact Non-U.S. Only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)