

Product Safety Data Sheet

XEROX

Product: 3400

PSDS No.: 0617
ISSUE DATE: 6/18/82
REV. DATE: 7/23/96

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Emergency No. EH&S Inquiries

(585) 422-2177 (800) 828-6571

Manufacturer's Address

Rochester, New York 14644

Product Designation

3400 Copier
3400 Sorter (10 Bin)
3400 Sorter (15 Bin)

Product Code

769
770
771

Section II - Electrical Information

Line Voltage

(Volts)
115 or 220

Line Current

(Amps)
15.5

Freq.

(Hertz)
60

Branch Cir. Protection

(Amps)
115V-20A sole use, 220V
Determined by local Code

Line Cord / Plug Specification

115V Single Phase 2 Wire + Ground
220V Single Phase 3 Wire + Ground
NEMA 5-20R
NEMA 14-30R

Power Consumption (Watts)*

Running: 1,740
Standby: 175

Agency Approvals

UL File Number E24014
CSA LR Number LR2196

Section III - Supplies

	Xerox Part No.
Dry Imager	6R47
Dry Toner (magnetic)	6R130
Developer	5R130
Photoreceptor	1R19

Material Safety Data Sheet

A-0009
A-0009A
B-0209A
Article ** (C2)

Section IV - Environmental Information

Product Size

(Centimeters / Inches)
D: 71 / 28
W: 109 / 43
H: 99 / 39

Heat Emission*

(BTU/HR)
Running: 7,620
Standby: 300

Environmental Limitations

	<u>Min</u>	<u>Max</u>
Relative Humidity (%)	15	85
Ambient Temp. (°C)	16	32

* Based on a five minute average

** MSDS is not required by OSHA Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2))

PRODUCT: 3400

PSDS No.0617

Floor Space Requirements

(Meter / Feet)

Stationary - 2.5 X 2.0 / 8.2 X 6.6

Movable - 1.8 X 1.4 / 5.9 X 4.6

Weight

(K Grams / Lbs.)

265 / 584

Section V - Emission/Exposure Information*

Light Source

Long Term Viewing of Exposure Lamp May Be Uncomfortable But Not Harmful

Electromagnetic Emissions

FCC: Class A

DOC: Class A

Audible Noise

Run 58.0 dB (A)

Impulse 62.0 dB (A)

TLV

85 dB (A)

Ozone

663 ug/min

0.077 ppm (TWA)

0.154 ppm (Peak)

TLV

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume 1741 copies/7.74 hours

Room Size 7.53 m³

1/2 Air Room Change per Hour

Total Dust

Total 0.11 mg/m³

TLV

10 mg/m³

Selenium

0.18 ug/m³

TLV

200 ug/m³

Arsenic

0.013 ug/m³

PEL

10 ug/m³

* Time weighted average (TWA) for normal, eight hour workday. TLV (Threshold Limit Value) and PEL (Permissible Exposure Level) respectively set by American Conference of Government Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposures permitted to ensure no health hazard.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.