

Product Safety Data Sheet

XEROX

Product: XC 810, XC 820, XC 830, XC 865, XC 1020,
XC 1040, XC 1044, XC1045, XC 1255

PSDS No.: 0767
ISSUE DATE 9/2/96
REV. DATE: 11/06/98

Section I - Product Identification

Manufacturer's Name
Xerox Corporation

Emergency No. EH&S Inquiries
(585) 422-2177 (800) 828-6571

Manufacturer's Address
Rochester, New York 14644

Product Designation
XC 810, XC 820, XC 830, XC 865, XC 1020,
XC 1040, XC 1044, XC1045, XC 1255

Product Identifier
US: E6T
Canada: E6T

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)
120	9.5	60

Branch Cir. Protection
(Amps)
15

Line Cord/Plug Specification
Single Phase 2 Wire + Ground
NEMA 5-15 P

Power Consumption (Watts)*
Run 372
Standby 30

Agency Approval
UL File Number E145607
CSA File Number LR23200

Section III - Supplies

	Xerox Part No.	Material Safety Data Sheet
Black Toner CRU	6R881	A0602
Copy Cartridge CRU	13R544	Article **

Section IV - Environmental Information

Product Size (Centimeters/ Inches)	Heat Emission* (BTU/HR)	Environmental Limitations	
		<u>Min</u>	<u>Max</u>
D: 47 / 8.5	Running: 1,272	Relative Humidity (%)	15 85
W: 47 / 8.5	Standby: 103	Ambient Temp. (°C)	10 32
H: 24.5 / 9.6			

Floor Space Requirements
(Meters Feet)
1 / 3.3
1 / 3.3

Weight
(K Grams / Lbs.)
38.1 / 17.2

* Based on a five minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29CFR or WHMIS HPA Section II (2).

Section V - Emission/Exposure Information**

Light Source

Tungsten Lamp - 200W

Electromagnetic Emissions

US FCC: Class B

Canada DOC: Class B

Audible Noise

Run 52.2 dB(A)

Standby 33.7 dB(A)

Impulse 60.3 dB(A)

TLV

85.0 dB(A)

Ozone

Concentration Based on Simulation Model:

Daily Copy Volume 25 copies/7.96 hours

Room Size 5.83 m³

1/2 Air Room Change per Hour

Ozone Filter Life - Life of Product

144.0 ug/min

0.006 ppm (TWA)

0.010 ppm (STEL)

TLV

0.1 ppm

Total Dust

0.09 mg/m³

TLV

10 mg/m³

* Based on a five minute average

** **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. TWA (Time Weighted Average) for normal, eight-hour workday. **STEL** (Short Term Exposure Level).

11/06/98

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.