

220V-240V 10 50/60 single

Product Safety Data Sheet

SDS # : 13-00591 2016-01-26 Revision 4

WorkCentre 5845

| Product Description | Multi-Function Equipment | |
|---|---|--|
| Speed (PPM) | 45 | |
| Mono / Color | Monochrome | |
| ELECTRICAL INPUT INFORMATION Voltage (Volts) Rated Current (Amperes): Frequency (Hertz) Phase Connection | 110V-127V 12 50/60 single | |

POWER AND HEAT

| | Power | Heat Output | Power | Heat Output |
|--|---------|-------------|---------|-------------|
| | (Watts) | (BTU/Hr) | (Watts) | (BTU/Hr) |
| Active ¹ | <1150 | <3922 | <1150 | <3922 |
| Ready ¹ | <240 | <818 | <240 | <818 |
| Sleep ¹ | <4.9 | <16.7 | <4.9 | <16.7 |
| Standby ¹ (Off/FEMP) ² | <0.9 | <3.1 | <0.9 | <3.1 |

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

| Relative Humidity % | 15-85% | | | |
|---------------------|----------|---|----------|----------|
| Ambient Temperature | 50-89 °F | / | 10-32 °C | |
| PRODUCT SIZE | | | | |
| Depth | 25.6 in. | | | 65.0 cm |
| Width | 23.4 in. | | | 59.5 cm |
| Height | 43.5 in. | | | 110.4 cm |
| Weight | 265 lbs | | | 120 kg |

SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

Class 1 Laser Product

CHEMICAL EMISSIONS

Chemical Emission Test Methodology RAL-UZ171 The machine was tested under the conditions as specified in the standard inside a room of 12.8 m³ with 1 air change per hour.

PARAMETER Total Volatile Organic C

Total Volatile Organic Compounds (TVOC) Dust Ozone

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

| Sound Power Level | |
|-------------------|--|
| LwAd (B) | |
| <5.0 | |
| 6.9 | |

Monochrome

Emission Rate

6.893 mg/h

3.566 mg/h

0.590 mg/h

Sound Pressure Level LpAd (dBA) <35 51.2

Standby Run - continuous



Product Safety Data Sheet

SUPPLIES

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issaunce of this Product Safety Data Sheet, Xerox does not asume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Contact U.S. Only: usa.xerox.EHS@xerox.com Contact Non-U.S. Only: ehs-europe@xerox.com