



Product Safety Data Sheet

SDS #: 17-00667

2017-07-14

Revision 1

Xerox® VersaLink C505

Product Identifier

Speed (PPM)

Mono / Color

Multi-Function Equipment / J-B291

45

Colour

ELECTRICAL INPUT INFORMATION

Voltage (Volts)

110V-127V

220V-240V

Rated Current (Amperes):

12

8

Frequency (Hertz)

50/60

50/60

Phase Connection

single

single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	730.0	2488.6	740.0	2522.7
Ready ¹	89.0	303.4	87.0	296.6
Sleep ¹	22.0	75.0	22.0	75.0
Sleep 2 ¹	0.9	3.1	0.9	3.1
Standby ¹ (Off/FEMP) ²	0.2	0.7	0.3	1.0

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %

15-85%

Ambient Temperature

41-90 °F

/

5-32 °C

PRODUCT SIZE

Depth

19.8 in.

50.3 cm

Width

18.5 in.

47.0 cm

Height

25.4 in.

64.4 cm

Weight

77 lbs

35.0 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

LED

CHEMICAL EMISSIONS

Chemical Emission Test Methodology RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 5.1 m³ with 1 air change per hour.

PARAMETER

Emission Rate

Total Volatile Organic Compounds (TVOC)

7.1 mg/h

Dust

0.30 mg/h

Ozone

0.23 mg/h

Styrene

0.075 mg/h

Benzene

0.0059 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	4.90	33.6
Run - continuous	7.17	56.2



Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177
Inquiries US only: 1-800-828-6571
Contact US only: usa.xerox.EHS@xerox.com
Contact Non US only: ehs-europe@xerox.com