

# **Product Safety Data Sheet**

**SDS # :** 17-00674 2017-10-17 Revision 1

# Xerox® VersaLink B610 Printer

## **Product Description**

Speed (PPM) Mono / Color Printer D-A280, D-B280 65 Monochrome

## ELECTRICAL INPUT INFORMATION

Voltage (Volts) Rated Current (Amperes) Frequency (Hertz) Phase Connection

12 50/60 single

110V-127V

220V-240V 8 50/60 single

# POWER AND HEAT

	Power	Heat Output	Power	Heat Output
	(Watts)	(BTU/Hr)	(Watts)	(BTU/Hr)
Active <sup>1</sup>	820	2798.0	830	2832.1
Ready <sup>1</sup>	66	225.2	65	221.8
Sleep <sup>1</sup>	11	37.5	12	40.9
Sleep (2) <sup>1</sup>	0.9	3.07	0.9	3.07
Standby <sup>1</sup> (Off/FEMP) <sup>2</sup>	0.2	0.68	0.2	0.68

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

# OPERATING ENVIRONMENT

10-85%			
50-90 °F	/	10-32 °C	
18.3 in.			46.6 cm
16.8 in.			42.7 cm
17.5 in.			44.3 cm
49.2 lbs			22.3 kg
	50-90 °F 18.3 in. 16.8 in. 17.5 in.	50-90 °F / 18.3 in. 16.8 in. 17.5 in.	50-90 °F / 10-32 ℃ 18.3 in. 16.8 in. 17.5 in.

## SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

# LIGHT SOURCE

Class 1 Laser Product

## **CHEMICAL EMISSIONS**

Chemical Emission Test Method RAL-UZ171 The machine was tested under the conditions as specified in the standard inside a room of 4.0 m<sup>3</sup> with 1.0 air changes per hour.

**EMISSION RATE** 

1.6 mg/h

0.2 mg/h

0.1 mg/h

0.022 mg/h 0.0064 mg/h

## PARAMETER

#### TVOC Dust Ozone Styrene Benzene

## ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	4.2	27.1
Run	6.9	56.8



# **Product Safety Data Sheet**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376 Contact U.S. Only: askxerox@xerox.com Contact Non-U.S. Only: ehs-europe@xerox.com