



Product Safety Data Sheet

SDS #: 17-00670

2017-07-14

Revision 1

Xerox® AltaLink® B8045 / B8055 / B8065 / B8075 / B8090

Product Identifier

Speed (PPM)

Mono / Color

Multi-Function Equipment BBA-1 / BBA-2 / BBB-1 / BBB-2

45/55/65/75/90

Monochrome

ELECTRICAL INPUT INFORMATION

Voltage (Volts)

Rated Current (Amperes):

Frequency (Hertz)

Phase Connection

110V-127V

12/16

60

single

200V-240V

8

50/60

single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	1315	4487	1285	4385
Ready ¹	81.6	278	78.3	267
Sleep ¹	3.95	13.5	3.92	13.4
Standby ¹ (Off/FEMP) ²	0.108	0.368	0.156	0.532

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %

15-85%

Ambient Temperature

50-90 °F / 10-32 °C

PRODUCT SIZE

Depth

26.1 in.

66.5 cm

Width

33.5 in.

85 cm

Height

47.2 in.

120 cm

Weight

264.5 lbs

120 kg

SPACE REQUIREMENTS

Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

LED

CHEMICAL EMISSIONS

Chemical Emission Test Methodology

RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 57.5 m³ with 2 air changes per hour.

PARAMETER

Total Volatile Organic Compounds (TVOC)

Dust

Ozone

Styrene

Benzene

Emission Rate

3.915 mg/h

None detected

0.149 mg/h

0.2510 mg/h

0.016 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	4.9	30.8
Run - continuous	7.5	74.9

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The



Product Safety Data Sheet

information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177
Inquiries US only: 1-800-828-6571
Contact US only: usa.xerox.EHS@xerox.com
Contact Non US only: ehs-europe@xerox.com