



Product Safety Data Sheet

SDS #: 17-00672

2017-07-14

Revision 1

Xerox® VersaLink B605 Multifunction

Product Description

Multifunction Equipment

D-A281, D-B281

Speed (PPM)

58

Mono / Color

Monochrome

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)	12	8
Rated Current (Amperes)	50/60	50/60
Frequency (Hertz)	single	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	820	2798.0	810	2763.8
Ready ¹	79	269.6	73	249.1
Sleep ¹	13	44.4	14	47.8
Sleep (2) ¹	0.9	3.07	1.0	3.4
Standby ¹ (Off/FEMP) ²	0.2	0.68	0.3	1.02

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	10-85%
Ambient Temperature	50-90 °F / 10-32 °C

PRODUCT SIZE

Depth	19.8 in.	50.3 cm
Width	18.5 in.	47.0 cm
Height	25.3 in.	64.4 cm
Weight	67.2 lbs	30.5 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

Class 1 Laser Product

CHEMICAL EMISSIONS

Chemical Emission Test Method RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 4.0 m³ with 1.0 air changes per hour.

PARAMETER

EMISSION RATE

TVOC	1.8 mg/h
Dust	0.19 mg/h
Ozone	0.12 mg/h
Styrene	0.059 mg/h
Benzene	0.0008 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	4.3	28.5
Run	6.9	57.9



Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com