

MATERIAL SAFETY DATA SHEET

F73L1502
02 00

D-4001
Part# 93K06201

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

F73L1502

HMIS CODES

| | |
|--------------|----|
| Health | 2* |
| Flammability | 0 |
| Reactivity | 0 |

PRODUCT NAME

POLANE* W2 Coating, Celestial Blue Xerox

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917

DATE OF PREPARATION

30-MAY-03

INFORMATION TELEPHONE NO.
(216) 566-2902

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

| % by WT | CAS No. | INGREDIENT | UNITS | VAPOR PRESSURE |
|---------|------------|-----------------------------------|-----------------------------|----------------|
| 7 | 29911-28-2 | 1-(2-Butoxymethylethoxy)-propanol | | 0.06 mm |
| | | ACGIH TLV Not Available | | |
| | | OSHA PEL Not Available | | |
| 2 | 112-34-5 | 2-(2-Butoxyethoxy)-ethanol | | 0.06 mm |
| | | ACGIH TLV Not Available | | |
| | | OSHA PEL Not Available | | |
| 2 | 13463-67-7 | Titanium Dioxide | | |
| | | ACGIH TLV | 10 mg/m3 as Dust | |
| | | OSHA PEL | 10 mg/m3 Total Dust | |
| | | OSHA PEL | 5 mg/m3 Respirable Fraction | |
| 0.4 | 1333-86-4 | Carbon Black | | |
| | | ACGIH TLV | 3.5 mg/m3 | |
| | | OSHA PEL | 3.5 mg/m3 | |

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

=====
 Section 4 -- FIRST AID MEASURES
 =====

If INHALED: If affected, remove from exposure. Restore breathing.
 Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water.
 Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes.
 Get medical attention.

If SWALLOWED: Do not induce vomiting.
 Get medical attention immediately.

 =====
 Section 5 -- FIRE FIGHTING MEASURES
 =====

| | | |
|----------------|------|------|
| FLASH POINT | LEL | UEL |
| Not Applicable | N.A. | N.A. |

FLAMMABILITY CLASSIFICATION

Not Applicable

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

 =====
 Section 6 -- ACCIDENTAL RELEASE MEASURES
 =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

 =====
 Section 7 -- HANDLING AND STORAGE
 =====

STORAGE CATEGORY

Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

=====
 Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION
 =====

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

 =====
 Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES
 =====

| | | |
|--|-------------------|--|
| PRODUCT WEIGHT | 8.68 lb/gal | 1039 g/l |
| SPECIFIC GRAVITY | 1.04 | |
| BOILING POINT | 212 - 449 F | 100 - 231 C |
| MELTING POINT | Not Available | |
| VOLATILE VOLUME | 72 % | |
| EVAPORATION RATE | Slower than ether | |
| VAPOR DENSITY | Heavier than air | |
| SOLUBILITY IN WATER | N.A. | |
| pH | 8.0 | |
| VOLATILE ORGANIC COMPOUNDS (VOC Theoretical) | | |
| 2.29 lb/gal | 274 g/l | Less Water and Federally Exempt Solvents |
| 0.90 lb/gal | 108 g/l | Emitted VOC |

 =====
 Section 10 -- STABILITY AND REACTIVITY
 =====

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

=====
 HAZARDOUS POLYMERIZATION

 Will not occur
 =====

 Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.

TOXICOLOGY DATA

| CAS No. | Ingredient Name | | | | |
|------------|-----------------------------------|------|-----|-----|---------------|
| 29911-28-2 | 1-(2-Butoxymethylethoxy)-propanol | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| | | | | | |
| 112-34-5 | 2-(2-Butoxyethoxy)-ethanol | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | 5660 mg/kg |
| | | | | | |
| 13463-67-7 | Titanium Dioxide | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| | | | | | |
| 1333-86-4 | Carbon Black | LC50 | RAT | 4HR | Not Available |
| | | LD50 | RAT | | Not Available |
| | | | | | |

 =====

 Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

 No data available.
 =====

 Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

 =====

 Section 14 -- TRANSPORT INFORMATION

 No data available.
 =====

 Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No. | CHEMICAL/COMPOUND | % by WT | % Element |
|---------|-------------------|---------|-----------|
| | Glycol Ethers | 2 | |

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.