



Product Safety Data Sheet

SDS # : 16-00648

2016-09-14

Revision 1

Phaser 6510

Product Description
Speed (PPM)
Mono / Color

Printer
30
Color

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)		
Rated Current (Amperes)	11	6
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	380.0	1295.4	350.0	1193.2
Ready ¹	41.0	139.8	44.0	150.0
Sleep ¹	12.0	40.9	14.0	47.7
Sleep (2) ¹	0.9	3.1	1.0	3.4
Standby ¹ (Off/FEMP) ²	0.2	0.7	0.3	1.0

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	15-85%	
Ambient Temperature	41-90 °F	/ 5-32 °C

PRODUCT SIZE

Depth	19.0 in.	48.3 cm
Width	16.5 in.	42.0 cm
Height	13.7 in.	34.7 cm
Weight	53 lbs	23.8 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

LED

CHEMICAL EMISSIONS

Chemical Emission Test Method RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 5.1 m³ with 1 air change per hour.

PARAMETER

EMISSION RATE

TVOC	2.3 mg/h
Dust	None detected
Ozone	None detected

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	4.01	24.9
Run	6.76	51.9



Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com