



Product Safety Data Sheet

SDS #: 17-00671

2017-07-14

Revision 1

Xerox® VersaLink B600 Printer

Product Description

Printer
D-A280, D-B280
58
Monochrome

Speed (PPM)
Mono / Color

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)	12	8
Rated Current (Amperes)	50/60	50/60
Frequency (Hertz)	single	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	840	2866.2	790	2695.6
Ready ¹	72	245.7	63	215.0
Sleep ¹	11	37.5	12	40.9
Sleep (2) ¹	0.9	3.07	0.9	3.07
Standby ¹ (Off/FEMP) ²	0.2	0.68	0.3	1.02

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	10-85%	
Ambient Temperature	50-90 °F	/ 10-32 °C

PRODUCT SIZE

Depth	18.3 in.	46.6 cm
Width	16.8 in.	42.7 cm
Height	17.5 in.	44.3 cm
Weight	49.2 lbs	22.3 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

Class 1 Laser Product

CHEMICAL EMISSIONS

Chemical Emission Test Method RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 4.0 m³ with 1.0 air changes per hour.

PARAMETER

EMISSION RATE

TVOC	1.6 mg/h
Dust	0.2 mg/h
Ozone	0.1 mg/h
Styrene	0.022 mg/h
Benzene	0.0064 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	4.2	26.9
Run	7.0	56.8



Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com