



Number: 2-0315
 Issue No: 1 (AO 3724)
 Date: June 2001
 Page: 1 of 2

Product Safety Data Sheet
Phaser 3400

PRODUCT DESCRIPTION

Phaser 3400 Black and White Laser Printer

	Standard	Certifying Body	Report Reference/ Licence
<u>ELECTRICAL & MECHANICAL CERTIFICATION</u>	IEC60950: 1991 +A1:1995, A2:1993, A3:1995, A4:1996	TUV	TBD
<u>ELECTRO-MAGNETIC COMPATIBILITY</u>	89/336/EEC including EN55022 Class B	SAMSUNG	M310

HEAT OUTPUT

Low Power Mode BTU	Standby (Average) BTU	Running (Average) BTU
36	72	870

POWER

Low Power Mode Watts	Standby (Average) Watts	Running (Average) Watts
12	24	290

POWER REQUIREMENTS

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

ENVIRONMENTAL LIMITATIONS (OPERATIONAL)

Relative Humidity (%):

20-80

Ambient Temperature (°C):

10 - 30

LIGHT SOURCE

Class 1 Laser Product

AUDIBLE NOISE

Operating Conditions	Sound Pressure - dB (A) Operator Position	Sound Power B (A)
Standby	38.5	4.5
Continuous	52.8	5.9
Impulse	60.2	6.7



Product Safety Data Sheet
Phaser 3400

Number: 2-0315
Issue No: 1 (AO 3724)
Date: June 2001
Page: 2 of 2

GASEOUS AND PARTICULATE EMISSIONS

Particulates:

total dust	TBD	mg/m ³	†
------------	-----	-------------------	---

Vapours & Gases:

Ozone	TBD	µg/min	
toner volatiles	TBD	ppm	‡

Notes

TBD To be determined

OZONE FILTER REPLACEMENT

Not applicable

PRODUCT DIMENSIONS

Depth	362 mm
Width	409 mm
Height	299 mm

SPACE REQUIREMENTS *[Minimum requirements are listed]*

NA Desktop product

WEIGHT

11 kg