

Product Safety Data Sheet

XEROX

Product: 5385/RDH

PSDS No.: 0717

ISSUE DATE: 12/02/93

REV. DATE: 03/27/02

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Manufacturer's Address

Rochester, New York 14644

Product Designation

5385

Emergency No.

(585) 422-2177

EH&S Inquiries

(800) 828-6571

Product Code

US: 87Y

Canada: 91Y

Section II - Electrical Information

Line Voltage

(Volts)

120

Line Current

(Amps)

24

Freq.

(Hertz)

60

Branch Cir. Protection

(Amps)

30A Sole use

Line Cord/Plug Specification

Single Phase 2 Wire & Ground

NEMA: 5-30R

Power Consumption(Watt)*

Standby: 409

Low Power: 233

Run: 2,083

Agency Approvals

UL File Number - E51242

CSA LR Number - LR90406

Section III - Supplies

Xerox Part No.

US

Canada

Toner/Black

6R382

6R569

Toner/Red

6R355

6R565

Toner/Blue

6R356

6R566

Toner/Green

6R357

6R567

Toner/Brown

6R358

6R568

Developer/Black

5R195

5R542

Developer/Red

5R196

5R543

Developer/Blue

5R197

5R546

Developer/Green

5R198

5R544

Developer/Brown

5R199

5R545

Photoreceptor

1R115

Article** (C10)

Fuser Oil Donor Roll

22K84501

D-0407

Material Safety Data Sheet

Section IV - Environmental Information

Product Size

(Centimeters / Inches)

D: 77 / 30

W:191 / 75

H: 133 / 52

Heat Emission*

(BTU/HR)

Running: 7,106

Standby: 1,395

Low Power: 794

Environmental Limitations

Min. Relative Humidity (15%) 50° F (10° C)

Max. Relative Humidity (60%) 90° F(32° C)

Ambient Temp.75° F (25° C)

* Based on a five minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29 CFR or WHMIS HPA Section II (2)

Product: 5385/RDH

PSDS No.: 0717

Section IV - Environmental Information

Floor Space Requirements

(Meters / Feet)

Stationary 3 x 3 / 10 x 10

Movable 3 x 2 / 10 x 8

Weight

(K Grams / Lbs.)

514 / 133

Section V - Emission/Exposure Information**

Light Source

Tungsten

Electromagnetic Emissions

US FCC: Class A

Canada DOC: Class A

Audible Noise

Run: 62.0 dB(A)

Standby: 34.6 dB(A)

Impulse: 75.5 dB(A)

TLV

85.0 dB(A)

Ozone

Concentration Based on Simulation Model:

Daily Copy Volume 3,250 Copies/min. 80

Room Size 12.1 m³

1/2 Air Room Change per Hour

Ozone Filter Part Number 53K90400

Ozone Filter Replacement Interval 450K Copies

0.008 ppm(TWA)

0.012 ppm(Peak)

TLV

0.1 ppm

Total Dust

<0.015 mg/m³

TLV

10 mg/m³ total

Silicone Oil

0.004 mg/m³

XEL

0.4 mg/m³

Toluene

47.2 ppb

TLV

50 ppm

VI - Product Recycling and Disposal

Xerox operates a worldwide equipment takeback and reuse/recycle program. Contact your Xerox sales representative (1-800-ASK-XEROX) to determine whether this Xerox product is part of the program. For more information about Xerox environmental programs, visit www.xerox.com (refer to "About Xerox" section). If your product is not part of the Xerox program and you are managing its disposal, please note that the product may contain lead, mercury and other materials whose disposal may be regulated due to environmental considerations. For recycling and disposal information, contact your local authorities. In the United States, you may also refer to the Electronic Industries Alliance web site: www.eiae.org.

* Based on a five minute average.

** **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.

www.xerox.com Reference "About Xerox"