



Product Safety Data Sheet

SDS # : 13-00600
2015-12-01
Revision 3

WorkCentre 7220 WorkCentre 7220i

Product Description

Speed (PPM)
Mono / Color

Multi-Function Equipment
20
Colour

ELECTRICAL INPUT INFORMATION

| | 110V-127V | 220V-240V |
|--------------------------|-----------|-----------|
| Voltage (Volts) | | |
| Rated Current (Amperes): | 12 | 8 |
| Frequency (Hertz) | 50/60 | 50/60 |
| Phase Connection | single | single |

POWER AND HEAT

| | Power (Watts) | Heat Output (BTU/Hr) | Power (Watts) | Heat Output (BTU/Hr) |
|--|------------------|-------------------------|------------------|-------------------------|
| Active ¹ | 402 | 1371 | 389 | 1326 |
| Ready ¹ | 111 | 378 | 111 | 378 |
| Sleep ¹ | 72 | 245 | 66 | 225 |
| Sleep 2 ¹ | 4.4 | 15 | 4.8 | 16 |
| Standby ¹ (Off/FEMP) ² | 0.07 | 0.2 | 0.32 | 1 |

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

| | | | |
|---------------------|----------|---|----------|
| Relative Humidity % | 20-80% | | |
| Ambient Temperature | 50-90 °F | / | 10-32 °C |

PRODUCT SIZE

| | | |
|--------|-----------|----------|
| Depth | 25.2 in. | 64.0 cm |
| Width | 23.0 in. | 58.5 cm |
| Height | 44.57 in. | 113.2 cm |
| Weight | 251.3 lbs | 114 kg |

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

Class 1 Laser product containing an embedded Class 3B Laser

CHEMICAL EMISSIONS

Chemical Emission Test Methodology RAL - UZ122

The machine was tested under the conditions as specified in the standard inside a room of 5 m³ with 1 air change per hour.

PARAMETER

Total Volatile Organic Compounds (TVOC)
Dust
Ozone

Colour
Emission Rate
0.099 mg/h
0.89 mg/h
None detected

ACOUSTICAL NOISE

| | Sound Power Level LwAd (B) | Sound Pressure Level LpAd (dBA) |
|------------------|-------------------------------|------------------------------------|
| Standby | 4.26 | 26.7 |
| Run - continuous | 6.96 | 52 |



Product Safety Data Sheet

SUPPLIES

MSDS Number(s) [Europe only]

A-1076, A-1077, A-1078, 1-1079

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Contact U.S. Only: usa.xerox.EHS@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com