

Product Safety Data Sheet

SDS #: 13-00597

2019-09-12

Revision 1

Xerox Color J75 Press

Product Identifier	Multi-Function Equipment / J-B190
Speed (PPM)	75 / 75
Mono / Color	Mono / Color

ELECTRICAL INPUT INFORMATION

Voltage (Volts)	208V-240V	-
Rated Current (Amperes):	12	-
Frequency (Hertz)	50/60	-
Phase Connection	single	-

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	1315	4471	-	-
Ready ¹	233	792	-	-
Sleep ¹	115	391	-	-
Sleep 2 ¹	2.29	7.8	-	-
Standby ¹ (Off/FEMP) ²	1.2	4	-	-

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	15-85
Ambient Temperature	50-95 °F / 10-35 °C

PRODUCT SIZE

Depth	305.91 in.	777 cm
Width	1637.01 in.	4158 cm
Height	539.37 in.	1370 cm
Weight	1445.4 lbs	657 kg

SPACE REQUIREMENTS

Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

Class 1 Laser product containing an embedded Class 3B Laser

Chemical Emission Test Methodology RAL - UZ122

The machine was tested under the conditions as specified in the standard inside a room of 2 m³ with 350 2 air changes per hour.

PARAMETER

	Emission Rate Colour	Emission Rate Monochrome
Total Volatile Organic Compounds (TVOC)	11 mg/h	15 mg/h
Dust	<0.68 mg/h	<2.3 mg/h
Ozone	<0.7 mg/h	<0.7 mg/h
Styrene	0.085 mg/h	0.094 mg/h
Benzene	0.045 mg/h	0.054 mg/h



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level LpAd (dBA)
Standby	5.3	35
Run - continuous	8.2	62

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Emergencies US only: 1-585-422-2177
Inquiries US only: 1-800-828-6571
Contact US only: usa.xerox.EHS@xerox.com
Contact Non US only: ehs-europe@xerox.com