



## Product Safety Data Sheet

SDS # : 18-00681

2018-01-18

Revision 1

# Xerox® AltaLink® C8045 Color Multifunction Printer

### Product Identifier

Multi-Function Equipment

J-A331

J-B331

### Speed (PPM)

45

### Mono / Color

Colour

### ELECTRICAL INPUT INFORMATION

Voltage (Volts)

110V-127V

220V-240V

Rated Current (Amperes):

12/16

8/10

Frequency (Hertz)

50/60

50/60

Phase Connection

single

single

### POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active <sup>1</sup>	739.4	2521.3	760.8	2594.3
Ready <sup>1</sup>	70.9	241.8	70.5	240.4
Sleep <sup>1</sup>	62.7	213.8	60.2	205.3
Sleep 2 <sup>1</sup>	3.78	12.9	3.63	12.4
Standby <sup>1</sup> (Off/FEMP) <sup>2</sup>	0.072	0.245	0.324	1.10

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

Relative Humidity %

15-85%

Ambient Temperature

50-90 °F / 10-32 °C

### PRODUCT SIZE

Depth	28.9 in.	73.4 cm
Width	43.6 in.	110.7 cm
Height	45.2 in.	114.8 cm
Weight	275.5 lbs	125 kg

### SPACE REQUIREMENTS

Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE:

LED

### CHEMICAL EMISSIONS

Chemical Emission Test Methodology

RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 57.5 m<sup>3</sup> with 2 air changes per hour.

### PARAMETER

Total Volatile Organic Compounds (TVOC)

### Colour Emission Rate

5.57 mg/h

### Monochrome Emission Rate

3.02 mg/h

Dust

0.113 mg/h

0.190 mg/h

Ozone

0.136 mg/h

0.109 mg/h

Styrene

0.096 mg/h

0.055 mg/h

Benzene

0.016 mg/h

0.011 mg/h

### ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level LpAd (dBA)
Standby	3.35	15.5
Run - continuous	6.64	49.3



## Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177  
Inquiries US only: 1-800-828-6571  
Contact US only: [usa.xerox.EHS@xerox.com](mailto:usa.xerox.EHS@xerox.com)  
Contact Non US only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)