



Product Safety Data Sheet

SDS # : 18-00686

2018-06-28

Revision 1

Xerox B1025 Multifunction Printer

Product Description

Speed (PPM)

Mono / Color

Multi-Function Equipment

25

Monochrome

ELECTRICAL INPUT INFORMATION

Voltage (Volts)

110V-127V

220V-240V

Rated Current (Amperes):

6.5

4

Frequency (Hertz)

50/60

50/60

Phase Connection

single

single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	432.8	1475.4	432.8	1475.4
Ready ¹	67.8	231.1	67.8	231.1
Sleep ¹	9.9	33.7	9.9	33.7
Sleep 2 ¹	1.3	4.4	1.3	4.4
Standby ¹ (Off/FEMP) ²	0.1	0.3	0.1	0.3

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %

15-85%

Ambient Temperature

41-90 °F / 5-32 °C

PRODUCT SIZE

Depth

23.6 in.

59.9 cm

Width

22.1 in.

56.0 cm

Height

19.9 in.

50.6 cm

Weight

67 lbs

30.4 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

Class 1 Laser Product

CHEMICAL EMISSIONS

Chemical Emission Test Methodology

RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 5.1 m³ with 1 air change per hour.

PARAMETER

Emission Rate

Total Volatile Organic Compounds (TVOC)

2.3 mg/h

Dust

1.49 mg/h

Ozone

0.3 mg/h

Styrene

0.41 mg/h

Benzene

0.001 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Run - continuous	6.4	49.3



Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177
Inquiries US only: 1-800-828-6571
Contact US only: usa.xerox.EHS@xerox.com
Contact Non US only: ehs-europe@xerox.com