



Product Safety Data Sheet

SDS #: 18-00689

2018-10-30

Revision 1

Xerox® VersaLink C8000

Product Description / Product Identifier

Speed (PPM)

Mono / Color

Printer / J-A340, J-B340

45

Color

ELECTRICAL INPUT INFORMATION

Voltage (Volts)

Rated Current (Amperes)

Frequency (Hertz)

Phase Connection

110V-127V

12

50/60

single

220V-240V

10

50/60

single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	810	2763.7	810	2763.7
Ready ¹	75	255.9	74	252.5
Sleep ¹	50	170.6	51	174.0
Sleep (2) ¹	0.5	1.71	0.5	1.71
Standby ¹ (Off/FEMP) ²	0.03	0.10	0.07	0.24

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %

10-85%

Ambient Temperature

50-90 °F

/

10-32 °C

PRODUCT SIZE

Depth

28.5 in.

72.5 cm

Width

24.4 in.

62.0 cm

Height

28.3 in.

72.0 cm

Weight

178.1 lbs

80.8 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

LED

CHEMICAL EMISSIONS

Chemical Emission Test Method

RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m³ with 4.0 air changes per hour.

PARAMETER

TVOC

Dust

Ozone

Styrene

Benzene

Emission Rate

7.0 mg/h

0.09 mg/h

0.17 mg/h

0.05 mg/h

0.01 mg/h



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	3.2	-
Run	7.3	66.3

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com