

## Product Safety Data Sheet

SDS # : 20-00698

2020-01-28

Revision 1

# AltaLink B8145

|                           |  |
|---------------------------|--|
| <b>Product Identifier</b> | Multi-Function Equipment D-A501 / D-B501 |
| <b>Speed (PPM)</b>        | 45                                       |
| <b>Mono / Color</b>       | Monochrome                               |

### ELECTRICAL INPUT INFORMATION

|                          | 110V-127V | 220V-240V |
|--------------------------|-----------|-----------|
| Voltage (Volts)          |           |           |
| Rated Current (Amperes): | 12        | 8         |
| Frequency (Hertz)        | 50/60     | 50/60     |
| Phase Connection         | single    | single    |

### POWER AND HEAT

|  | Power<br>(Watts) | Heat Output<br>(BTU/Hr) | Power<br>(Watts) | Heat Output<br>(BTU/Hr) |
|--|------------------|-------------------------|------------------|-------------------------|
| Active <sup>1</sup>                          | 713              | 2433                    | 696              | 2374                    |
| Ready <sup>1</sup>                           | 66.3             | 226.2                   | 66.3             | 226.2                   |
| Sleep <sup>1</sup>                           | 0.69             | 2.34                    | 0.74             | 2.52                    |
| Standby <sup>1</sup> (Off/FEMP) <sup>2</sup> | 0.02             | 0.08                    | 0.06             | 0.2                     |

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

|                     |          |            |
|---------------------|----------|------------|
| Relative Humidity % | 10-85%   |            |
| Ambient Temperature | 50-90 °F | / 10-32 °C |

### PRODUCT SIZE

|        |          |          |
|--------|----------|----------|
| Depth  | 28.5 in. | 72.3 cm  |
| Width  | 26.3 in. | 66.8 cm  |
| Height | 45.1 in. | 114.7 cm |
| Weight | 287 lbs  | 130 kg   |

### SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE:

LED

### CHEMICAL EMISSIONS

Chemical Emission Test Methodology RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m<sup>3</sup> with 4.0 air changes per hour.

### PARAMETER

| PARAMETER                               | Emission Rate |
|---|---------------|
| Total Volatile Organic Compounds (TVOC) | 1.0 mg/h      |
| Dust                                    | None detected |
| Ozone                                   | None detected |
| Styrene                                 | 0.03 mg/h     |
| Benzene                                 | 0.02 mg/h     |

### ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

|                  | Sound Power Level<br>LwAd (dBA) | Sound Pressure Level |
|------------------|---------------------------------|----------------------|
| Run - continuous | 65.0                            | -                    |



## Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177  
Inquiries US only: 1-800-828-6571  
Contact US only: [usa.xerox.EHS@xerox.com](mailto:usa.xerox.EHS@xerox.com)  
Contact Non US only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)