

Product Safety Data Sheet

SDS #: 20-00703

2020-01-28 Revision 1

AltaLink C8145

Product Identifier Multi-Function Equipment J-A271 / J-B271

Speed (PPM) 45 **Mono / Color** Colour

ELECTRICAL INPUT INFORMATION

 Voltage (Volts)
 110V-127V
 220V-240V

 Rated Current (Amperes):
 12
 8

 Frequency (Hertz)
 50/60
 50/60

 Phase Connection
 single
 single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	718	2449	675	2303
Ready ¹	71.4	243.6	71.2	243.0
Sleep ¹	0.67	2.29	0.71	2.44
Standby ¹ (Off/FEMP) ²	0.02	0.08	0.06	0.2

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity % 10-85% Ambient Temperature 50-90 °F / 10-32 °C

PRODUCT SIZE

 Depth
 28.5 in.
 72.3 cm

 Width
 26.3 in.
 66.8 cm

 Height
 45.1 in.
 114.7 cm

 Weight
 287 lbs
 130 kg

SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE: LED

CHEMICAL EMISSIONS

Chemical Emission Test Methodology RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m³ with 4.0 air changes per hour.

PARAMETEREmission RateTotal Volatile Organic Compounds (TVOC)2.0 mg/hDustNone detectedOzoneNone detectedStyrene0.1 mg/hBenzene0.01 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

Sound Power Level LwAd (dBA) **Sound Pressure Level**

Run - continuous

65.2

² FEMP - Federal Energy Management Program



Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177 Inquiries US only: 1-800-828-6571 Contact US only: usa.xerox.EHS@xerox.com Contact Non US only: ehs-europe@xerox.com