



Product Safety Data Sheet

Product: DocuColor 7000 / 8000 Digital Press
DocuColor 7000AP / 8000AP Digital Press

PSDS No.: 0952
ISSUE DATE: 09/01/04
REV. DATE: 06/04/07

Section I - Product Identification

Manufacturer's Name
Xerox Corporation

Emergency No.
(585) 422-2177

EH&S Inquires
(800) 828 -6571

Manufacturer's Address
Webster, NY 14580

Product Designation
DocuColor 7000 / 8000 Digital Press
DocuColor 7000AP / 8000AP Digital Press

Product Identifier:
System YNA-4

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)
208V	24A	60

Branch Cir. Protection
(Amps)
30A

Line Cord/Plug Specification
Three wire + Ground
NEMA Type 14-30 Plug

Power Consumption (Watts)*

Running:	3,190
Standby:	775
Power Saver:	12
OFF/FEMP:	0

Agency Approval
UL File Number E51242
cUL File Number E51242

Section III - Supplies

	Xerox Part No.	Material Safety Data Sheet
Toner, Black	6R1199	P-01
Toner, Cyan	6R1200	P-03
Toner, Magenta	6R1201	P-02
Toner, Yellow	6R1202	P-04
Developer, Black	5R629	B - 0311
Developer, Cyan	5R630	B - 0312
Developer, Magenta	5R631	B - 0313
Developer, Yellow	5R632	B - 0314
Fuser Agent	8R12965	D - 4004
Fuser Agent	8R13031	D - 4006

Section IV - Environmental Information

Product Size (IOT) (Meters / Inches)	Heat Emission* (BTU/HR)	Environmental Limitations	
		<u>Min</u>	<u>Max</u>
D: 1.1 / 43.3	Running: 10,880	Relative Humidity (%)	15 85
W: 4.0 / 156.5	Standby: 2,645	Ambient Temp. (°C)	10 32
H: 1.41/ 55.6	Power Saver: 41		

*Based on a five minute average

**Product: DocuColor 7000 / 8000 Digital Press
DocuColor 7000AP / 8000AP Digital Press**

PSDS No.: 0952

Floor Space Requirements

Full System (Meters / Feet)
2.9(D) X 7.1 (W) / 9.5 X 23

Weight

(K Grams / Lbs.)
IOT 1739 / 3834

Section V - Emission/Exposure Information*

Light Source

Class 3b Laser in a Class 1 Laser System,
registered with the US FDA

FDA Accession number

9922778-03

Electromagnetic Emissions

US FCC: Class A
Canada DOC: Class A

Audible Noise

Run 59.2 dB(A)
Standby 31.9 dB(A)
Impulse 61.6 dB(A)

TLV*

85.0 dB(A)

Ozone

Concentration Based on Simulation Model:

Daily Copy Volume 20,000 copies/ hours

Room Size 50 m³

0 Air Room Change per Hour

Ozone Filter – Replaceable every 400,000 impressions

Emission rate:

0.009 ppm

0.0015 mg/m³ (8 hr.TWA)

TLV

0.1 ppm

Total Dust

0.019 mg/m³

TLV

10 mg/m³

Section VI - Product Recycling and Disposal

Xerox operates a worldwide equipment takeback and reuse/recycle program. Contact your Xerox sales representative (1-800-ASK-XEROX) to determine whether this Xerox product is part of the program. For more information about Xerox environmental programs, visit www.xerox.com/environment.

If you are managing the disposal of your Xerox product, please note that the product contains lead and other materials whose disposal may be regulated due to environmental considerations. The presence of lead and mercury is fully consistent with global regulations applicable at the time that the product was placed on the market. For recycling and disposal information, contact your local authorities. In the United States, you may also refer to the Electronic Industries Alliance web site: www.eiae.org.

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time-Weighted Average) for a normal eight-hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.

www.xerox.com Reference "About Xerox"