

Product Safety Data Sheet

SDS #: 20-00701

2020-01-28

Revision 1

AltaLink C8130

Product Identifier
Speed (PPM)
Mono / Color

Multi-Function Equipment J-A270 / J-B270
 30
 Colour

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)		
Rated Current (Amperes):	12	8
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	576	1967	586	1999
Ready ¹	67.1	229.0	71.1	242.6
Sleep ¹	0.70	2.37	0.72	2.46
Standby ¹ (Off/FEMP) ²	0.02	0.08	0.06	0.2

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	10-85%
Ambient Temperature	50-90 °F / 10-32 °C

PRODUCT SIZE

Depth	28.5 in.	72.3 cm
Width	26.3 in.	66.8 cm
Height	45.1 in.	114.7 cm
Weight	287 lbs	130 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

LED

CHEMICAL EMISSIONS

Chemical Emission Test Methodology RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m³ with 4.0 air changes per hour.

PARAMETER

PARAMETER	Emission Rate
Total Volatile Organic Compounds (TVOC)	1.0 mg/h
Dust	None detected
Ozone	None detected
Styrene	0.03 mg/h
Benzene	0.01 mg/h

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (dBA)	Sound Pressure Level
Run - continuous	63.7	-



Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177
Inquiries US only: 1-800-828-6571
Contact US only: usa.xerox.EHS@xerox.com
Contact Non US only: ehs-europe@xerox.com