

## Product Safety Data Sheet

SDS #: 20-00710

2021-07-09

Revision 4

# Xerox® Versant™ 280 Press

|                            |         |
|----------------------------|---------|
| <b>Product Description</b> | Printer |
| <b>Speed (PPM)</b>         | 80      |
| <b>Mono / Color</b>        | Colour  |

### ELECTRICAL INPUT INFORMATION

|                          |           |   |
|--------------------------|-----------|---|
| Voltage (Volts)          | 200V-240V | - |
| Rated Current (Amperes): | 16-20A    | - |
| Frequency (Hertz)        | 50/60     | - |
| Phase Connection         | single    | - |

### POWER AND HEAT

|  | Power<br>(Watts) | Heat Output<br>(BTU/Hr) | Power<br>(Watts) | Heat Output<br>(BTU/Hr) |
|--|------------------|-------------------------|------------------|-------------------------|
| Active <sup>1</sup>                          | 1690             | 5770                    |                  |                         |
| Ready <sup>1</sup>                           | 435              | 1480                    |                  |                         |
| Sleep <sup>1</sup>                           | 154              | 525                     |                  |                         |
| Sleep 2 <sup>1</sup>                         | 1                | 3.4                     |                  |                         |
| Standby <sup>1</sup> (Off/FEMP) <sup>2</sup> | 0.04             | 0.1                     |                  |                         |

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

|                     |          |            |
|---------------------|----------|------------|
| Relative Humidity % | 15-85%   |            |
| Ambient Temperature | 50-90 °F | / 10-32 °C |

### PRODUCT SIZE

|        |         |          |
|--------|---------|----------|
| Depth  | 33 in.  | 83.1 cm  |
| Width  | 30 in.  | 76.0 cm  |
| Height | 48 in.  | 121.2 cm |
| Weight | 651 lbs | 295 kg   |

### SPACE REQUIREMENTS

Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE:

Class 1 Laser Product

### Chemical Emission Test Methodology RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 5.1 m<sup>3</sup> with 1 air changes per hour.

| PARAMETER                               | Emission Rate |
|---|---------------|
| Total Volatile Organic Compounds (TVOC) | 12 mg/h       |
| Dust                                    | 0.7 mg/h      |
| Ozone                                   | 1.9 mg/h      |
| Styrene                                 | 0.1 mg/h      |
| Benzene                                 | 0.06 mg/h     |



## Product Safety Data Sheet

### ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

|                  | <b>Sound Power Level</b><br><b>LwAd (B)</b> | <b>Sound Pressure Level</b><br><b>LpAd (dBA)</b> |
|------------------|---|--|
| Standby          | 5.6   | 37   |
| Run - continuous | 8.5   | 64   |

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Emergencies US only: 1-585-422-2177  
Inquiries US only: 1-800-828-6571  
Contact US only: [usa.xerox.EHS@xerox.com](mailto:usa.xerox.EHS@xerox.com)  
Contact Non US only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)