

Product Safety Data Sheet

SDS #: 21-00715

2021-02-04

Revision 2

Xerox® Baltoro™ HF Inkjet Press with Color Accelerator

Product Identifier
Speed (PPM)
Mono / Color

Production Printer BDC-3
 180
 Colour

ELECTRICAL INPUT INFORMATION

	120V/208V	220-240V/380-415V
Voltage (Volts)		
Rated Current (Amperes):	48A	25A
Frequency (Hertz)	60	50/60
Phase Connection	three	three

POWER AND HEAT

Printer

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	12885	43965	12575	42907
Ready ¹	2349	7984	2089	7128

POWER AND HEAT

Dryer

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	7813	26659	7875	26871
Ready ¹	1419	4842	1308	4464

OPERATING ENVIRONMENT

Relative Humidity %	35-55%	
Ambient Temperature	68-77 °F	/ 20-25 °C

PRODUCT SIZE

Depth	58 in.	147.32 cm
Width	260.5 in.	571.6 cm
Height	80 in.	203.2 cm
Weight	6651 lbs	3017 kg

SPACE REQUIREMENTS

Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

Class 1 Laser product containing an embedded Class 3B Laser

CHEMICAL EMISSIONS PARAMETER

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level LpAd (dBA)
Standby	-	68.0
Run - continuous	-	72.0



Product Safety Data Sheet

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Emergencies US only: 1-585-422-2177
Inquiries US only: 1-800-828-6571
Contact US only: usa.xerox.EHS@xerox.com
Contact Non US only: ehs-europe@xerox.com