

Product Safety Data Sheet

SDS #: 21-00720

2021-07-09

Revision 2

Xerox EC8036

Product Description / Product Identifier

Multifunction Equipment

J-A330

J-B330

Speed (PPM)

35

Mono / Color

Color

ELECTRICAL INPUT INFORMATION

| | 110V-127V | 220V-240V |
|-------------------------|-----------|-----------|
| Voltage (Volts) | 110/127 | 220/240 |
| Rated Current (Amperes) | 12/16 | 8/10 |
| Frequency (Hertz) | 50/60 | 50/60 |
| Phase Connection | single | single |

POWER AND HEAT

| | Power (Watts) | Heat Output (BTU/Hr) | Power (Watts) | Heat Output (BTU/Hr) |
|--|---------------|----------------------|---------------|----------------------|
| Active ¹ | 610 | 2081.3 | 620 | 2115.4 |
| Ready ¹ | 55 | 187.7 | 55 | 187.7 |
| Sleep ¹ | 40 | 136.5 | 40 | 136.5 |
| Sleep (2) ¹ | 1.1 | 3.75 | 1.3 | 4.4 |
| Standby ¹ (Off/FEMP) ² | 0.1 | 0.341 | 0.4 | 1.365 |

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

| | |
|---------------------|---------------------|
| Relative Humidity % | 15-85% |
| Ambient Temperature | 50-90 °F / 10-32 °C |

PRODUCT SIZE

| | | |
|--------|-----------|----------|
| Depth | 28.9 in. | 73.4 cm |
| Width | 43.6 in. | 110.7 cm |
| Height | 45.2 in. | 114.8 cm |
| Weight | 275.5 lbs | 125 kg |

SPACE REQUIREMENTS

Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

LED

Chemical Emission Test Method RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 57.5 m³ with 2 air changes per hour.

PARAMETER

| | Color Emission Rate | Monochrome Emission Rate |
|---------|---------------------|--------------------------|
| TVOC | 2.97 mg/h | 1.4 mg/h |
| Dust | 0.142 mg/h | 0.194 mg/h |
| Ozone | 0.167 mg/h | 0.132 mg/h |
| Styrene | 0.0413 mg/h | 0.028 mg/h |
| Benzene | 0.014 mg/h | 0.009 mg/h |



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

| | Sound Power Level LwAd (B) | Sound Pressure Level LpAd (dBA) |
|---------|---|--|
| Standby | 3.32 | 15.3 |
| Run | 6.42 | 47.2 |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com