

Product Safety Data Sheet

SDS #: 21-00721

2021-07-09

Revision 2

Xerox EC8056

Product Identifier

Multi-Function Equipment

J-A331

J-B331

Speed (PPM)

55

Mono / Color

Colour

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)	110/127	220/240
Rated Current (Amperes):	12/16	8/10
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	800	2729.6	800	2729.6
Ready ¹	85	290.0	100	341.2
Sleep ¹	45	153.5	50	170.6
Sleep 2 ¹	0.9	3.07	1.7	5.8
Standby ¹ (Off/FEMP) ²	0.1	0.341	0.4	1.365

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	15-85%
Ambient Temperature	50-90 °F / 10-32 °C

PRODUCT SIZE

Depth	28.9 in.	73.4 cm
Width	43.6 in.	110.7 cm
Height	45.2 in.	114.8 cm
Weight	275.5 lbs	125 kg

SPACE REQUIREMENTS

Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

LED

Chemical Emission Test Methodology RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 57.5 m³ with 2 air changes per hour.

PARAMETER

PARAMETER	Colour Emission Rate	Monochrome Emission Rate
Total Volatile Organic Compounds (TVOC)	5.57 mg/h	3.02 mg/h
Dust	0.113 mg/h	0.190 mg/h
Ozone	0.136 mg/h	0.109 mg/h
Styrene	0.096 mg/h	0.065 mg/h
Benzene	0.016 mg/h	0.011 mg/h



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level LpAd (dBA)
Standby	3.34	15.4
Run - continuous	6.81	50.8

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177
Inquiries US only: 1-800-828-6571
Contact US only: usa.xerox.EHS@xerox.com
Contact Non US only: ehs-europe@xerox.com