

Product Safety Data Sheet

SDS #: 22-00735

2022-02-22

Revision 1

Xerox® VersaLink C7130

Product Description

Multifunction Equipment

J-A464 / J-B464

Speed (PPM)

30

Mono / Color

Color

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)		
Rated Current (Amperes)	12	8
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	545	1859.6	539	1839.1
Ready ¹	89	303.7	89	303.7
Sleep ¹	67	228.6	64	218.4
Sleep (2) ¹	0.8	2.73	1.4	4.78
Standby ¹ (Off/FEMP) ²	0.1	0.34	0.4	1.36

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity %	10-85%
Ambient Temperature	50-90 °F / 10-32 °C

PRODUCT SIZE

Depth	26.4 in.	67.1 cm
Width	23.2 in.	59.0 cm
Height	30.2 in.	76.8 cm
Weight	147.7 lbs	67 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

LED

CHEMICAL EMISSIONS

Chemical Emission Test Method RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m³ with 4.0 air changes per hour.

PARAMETER

Emission Rate

TVOC	3.8 mg/h
Dust	None detected
Ozone	None detected
Styrene	None detected
Benzene	0.008 mg/h



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	4.0	24.7
Run	6.6	53.7

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com