



## Product Safety Data Sheet

SDS # : 17-00664

2017-05-16

Revision 1

# Xerox® VersaLink C7025 Multifunction Printer

### Product Description

Multi-Function Equipment

J-A310 / J-B310

### Speed (PPM)

25

### Mono / Color

Colour

### ELECTRICAL INPUT INFORMATION

Voltage (Volts)

110V-127V

220V-240V

Rated Current (Amperes):

12

8

Frequency (Hertz)

50/60

50/60

Phase Connection

single

single

### POWER AND HEAT

|  | Power<br>(Watts) | Heat Output<br>(BTU/Hr) | Power<br>(Watts) | Heat Output<br>(BTU/Hr) |
|--|------------------|-------------------------|------------------|-------------------------|
| Active <sup>1</sup>                          | 454              | 1549.1                  | 495              | 1689.0                  |
| Ready <sup>1</sup>                           | 89               | 303.7                   | 89               | 303.7                   |
| Sleep <sup>1</sup>                           | 67               | 228.6                   | 64               | 218.4                   |
| Sleep 2 <sup>1</sup>                         | 0.8              | 2.73                    | 1.4              | 4.78                    |
| Standby <sup>1</sup> (Off/FEMP) <sup>2</sup> | 0.1              | 0.34                    | 0.4              | 1.36                    |

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment: Version 1.2

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

Relative Humidity %

10-85%

Ambient Temperature

50-90 °F / 10-32 °C

### PRODUCT SIZE

Depth

26.4 in.

67.1 cm

Width

23.2 in.

59.0 cm

Height

30.2 in.

76.8 cm

Weight

147.7 lbs

67 kg

### SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE:

LED

### CHEMICAL EMISSIONS

Chemical Emission Test Methodology

RAL-UZ171

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m<sup>3</sup> with 4.0 air changes per hour.

### PARAMETER

### Emission Rate

Total Volatile Organic Compounds (TVOC)

3.8 mg/h

Dust

None detected

Ozone

None detected

Styrene

None detected

Benzene

0.008 mg/h

### ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

|                  | Sound Power Level<br>LwAd (B) | Sound Pressure Level<br>Lpam (dBA) |
|------------------|-------------------------------|------------------------------------|
| Standby          | 3.8                           | 19.9                               |
| Run - continuous | 6.4                           | 53.7                               |



## Product Safety Data Sheet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177  
Inquiries US only: 1-800-828-6571  
Contact US only: [usa.xerox.EHS@xerox.com](mailto:usa.xerox.EHS@xerox.com)  
Contact Non US only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)