

Product Safety Data Sheet

SDS # : 23-00741 2023-08-30 Revision 4

Xerox® VersaLink B625

Product Identifier Speed (PPM) Mono / Color	Multifunction Device (MFD) 7464-0e6 65 Monochrome				
ELECTRICAL INPUT INFORMATION Voltage (Volts) Rated Current (Amperes): Frequency (Hertz) Phase Connection	:	DV-127V 10.3 50/60 single	5	220V-240V 5.3 50/60 single	
POWER AND HEAT					
TEC Value (kWh/wk)	0.93		0.99		
Active ¹ Ready ¹ Sleep ¹ Standby ¹ (Off/FEMP) ²	Power (Watts) 860.7 37.4 1.7 0.2	Heat Output (BTU/Hr) 2936.7 127.6 5.8 0.68	Power (Watts) 806 42.9 1.8 0.2	Heat Output (BTU/Hr) 2750.1 146.4 6.1 0.68	

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment.

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity % Ambient Temperature	10-85 50-90		/	10-32 °C	
PRODUCT SIZE Depth Width Height Weight	22.8 22.0 29.1 97.2	in. in.			57.8 cm 55.9 cm 73.9 cm 44.1 kg

SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

Class 1 Laser Product

Chemical Emission Test Methodology DE-UZ-219

The machine was tested under the conditions as specified in the standard inside a room of 4.0 m³ with 1 air change per hour.

PARAMETER

Total Volatile Organic Compounds (TVOC)
Dust
Ozone
Styrene
Benzene

Emission Rate 3.316 mg/h 0.61 mg/h < Limit of detection 0.093 mg/h < Limit of detection



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level	Sound Pressure Level		
	LwAd (B)	Lpam (dBA)		
Standby	3.2	14.0		
Run - continuous	7.2	57.0		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177 Inquiries US only: 1-800-828-6571 Contact US only: usa.xerox.EHS@xerox.com Contact Non US only: ehs-europe@xerox.com