

## Product Safety Data Sheet

SDS #: 23-00745

2023-08-30

Revision 2

# Xerox® VersaLink B415 Multifunction Printer

### Product Identifier

Speed (PPM)

Mono / Color

Multi-Function Equipment / 7020-6e6

50

Monochrome

### ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)		
Rated Current (Amperes):	8.6	4.3
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

### POWER AND HEAT

TEC Value (kWh/wk)	0.66	0.71
--------------------	------	------

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active <sup>1</sup>	625.5	2134.2	610.0	2081.3
Ready <sup>1</sup>	15.0	51.2	16.4	56.0
Sleep <sup>1</sup>	1.3	4.4	1.6	5.5
Standby <sup>1</sup> (Off/FEMP) <sup>2</sup>	0.1	0.34	0.1	0.34

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

Relative Humidity %	15-80%
Ambient Temperature	50-90 °F / 10-32.2 °C

### PRODUCT SIZE

Depth	17.8 in.	45.2 cm
Width	18.9 in.	47.9 cm
Height	20.2 in.	51.4 cm
Weight	26.6 lbs	12.1 kg

### SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE:

Class 1 Laser Product

Chemical Emission Test Methodology DE-UZ-219

The machine was tested under the conditions as specified in the standard inside a room of 2.41 m<sup>3</sup> with 1.0 air changes per hour.

### PARAMETER

Total Volatile Organic Compounds (TVOC)

Dust

Ozone

Styrene

Benzene

### Emission Rate

9.133 mg/h

0.50 mg/h

< Limit of detection

0.074 mg/h

< Limit of detection



## Product Safety Data Sheet

### ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	3.1	6.6
Run - continuous	6.6	51.0

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Emergencies US only: 1-585-422-2177  
Inquiries US only: 1-800-828-6571  
Contact US only: [usa.xerox.EHS@xerox.com](mailto:usa.xerox.EHS@xerox.com)  
Contact Non US only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)