

Product Safety Data Sheet

SDS #: 23-00747

2023-10-31

Revision 1

VersaLink® B620 Printer

Product Description / Product Identifier

Speed (PPM)

Mono / Color

Printer / 4064-4e0

61

Monochrome

ELECTRICAL INPUT INFORMATION

| | 110V-127V | 220V-240V |
|-------------------------|-----------|-----------|
| Voltage (Volts) | | |
| Rated Current (Amperes) | 9.8 | 4.9 |
| Frequency (Hertz) | 50/60 | 50/60 |
| Phase Connection | single | single |

POWER AND HEAT

TEC Value (kWh/wk) 0.88 0.87

| | Power (Watts) | Heat Output (BTU/Hr) | Power (Watts) | Heat Output (BTU/Hr) |
|----------------------------------------------|---------------|----------------------|---------------|----------------------|
| Active ¹ | 715.0 | 2439.6 | 757 | 2582.9 |
| Ready ¹ | 34.9 | 119.1 | 37.6 | 128.3 |
| Sleep ¹ | 1.5 | 5.1 | 1.6 | 5.5 |
| Standby ¹ (Off/FEMP) ² | 0.3 | 1.02 | 0.3 | 1.02 |

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity % 10-85%
Ambient Temperature 50-90 °F / 10-32 °C

PRODUCT SIZE

| | | |
|--------|----------|---------|
| Depth | 20.1 in. | 51.0 cm |
| Width | 16.9 in. | 42.8 cm |
| Height | 17.5 in. | 44.5 cm |
| Weight | 56.0 lbs | 25.4 kg |

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE

Class 1 Laser Product

Chemical Emission Test Method DE-UZ-219

The machine was tested under the conditions as specified in the standard inside a room of 2.41 m³ with 1.0 air changes per hour.

PARAMETER

| PARAMETER | Emission Rate |
|-----------|----------------------|
| TVOC | 3.316 mg/h |
| Dust | 0.61 mg/h |
| Ozone | < Limit of detection |
| Styrene | 0.093 mg/h |
| Benzene | < Limit of detection |



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

| | Sound Power Level LwAd (B) | Sound Pressure Level Lpam (dBA) |
|---------|---------------------------------------------|--------------------------------------------------|
| Standby | 3.2 | 14.0 |
| Run | 7.3 | 57.0 |

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Inquiries U.S. Only: 1-800-275-9376
Contact U.S. Only: askxerox@xerox.com
Contact Non-U.S. Only: ehs-europe@xerox.com