

0.46

Product Safety Data Sheet

SDS #: 24-00750

2024-04-16 Revision 1

Xerox® C320

Product Identifier Printer 5031-2e0

Speed (PPM) 35 Mono / Color Colour

ELECTRICAL INPUT INFORMATION

 Voltage (Volts)
 110V-127V
 220V-240V

 Rated Current (Amperes):
 7.6
 3.8

 Frequency (Hertz)
 50/60
 50/60

 Phase Connection
 single
 single

POWER AND HEAT

| TEC value (kwn/wk) | | 0.46 | 0.46 | |
|--|------------------|-------------------------|------------------|-------------------------|
| | Power (Watts) | Heat Output (BTU/Hr) | Power (Watts) | Heat Output (BTU/Hr) |
| Active ¹ | 499.8 | 1705.3 | 493.4 | 1683.5 |
| Ready ¹ | 18.46 | 63.0 | 20.31 | 69.3 |
| Sleep ¹ | 1.0 | 3.4 | 1.0 | 3.4 |
| Standby ¹ (Off/FEMP) ² | 0.2 | 0.68 | 0.2 | 0.68 |

0.46

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

 Relative Humidity %
 10-85%

 Ambient Temperature
 50-90 °F / 10-32 °C

PRODUCT SIZE

 Depth
 16.6 in.
 42.3 cm

 Width
 17.9 in.
 45.5 cm

 Height
 12.5 in.
 31.8 cm

 Weight
 47.1 lbs
 21.4 kg

SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE: Class 1 Laser Product

Chemical Emission Test Methodology DE-UZ-219

The machine was tested under the conditions as specified in the standard inside a room of 2.41 m³ with 1.0 air changes per hour.

 PARAMETER
 Emission Rate

 Total Volatile Organic Compounds (TVOC)
 9.989 mg/h

 Dust
 0.31 mg/h

 Ozone
 < Limit of detection</td>

 Styrene
 0.30 mg/h

 Benzene
 < Limit of detection</td>

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment

² FEMP - Federal Energy Management Program



Product Safety Data Sheet

Tested in accordance to ISO 7779 and declared per ISO 9296

| | Sound Power Level | Sound Pressure Level | |
|------------------|-------------------|----------------------|--|
| | LwAd (dBA) | Lpam (dBA) | |
| Standby | 3.1 | 14 | |
| Run - continuous | 6.8 | 54 | |

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issaunce of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Emergencies US only: 1-585-422-2177 Inquiries US only: 1-800-828-6571 Contact US only: usa.xerox.EHS@xerox.com

Contact Non US only: ehs-europe@xerox.com