

## Product Safety Data Sheet

SDS #: 24-00750

11-Sep-2024

Revision 2

# Xerox® C320

### Product Description / Product Identifier

Speed (PPM)

Mono / Color

Printer 5031-2e0

35

Color

### ELECTRICAL INPUT INFORMATION

Voltage (Volts)

Rated Current (Amperes)

Frequency (Hertz)

Phase Connection

110V-127V

7.6

50/60

single

220V-240V

3.8

50/60

single

### POWER AND HEAT

TEC Value (kWh/wk)

0.46

0.46

|  | Power<br>(Watts) | Heat Output<br>(BTU/Hr) | Power<br>(Watts) | Heat Output<br>(BTU/Hr) |
|--|------------------|-------------------------|------------------|-------------------------|
| Active <sup>1</sup>                          | 499.8            | 1705.3                  | 493.4            | 1683.5                  |
| Ready <sup>1</sup>                           | 18.46            | 63.0                    | 20.31            | 69.3                    |
| Sleep <sup>1</sup>                           | 1.0              | 3.4                     | 1.0              | 3.4                     |
| Standby <sup>1</sup> (Off/FEMP) <sup>2</sup> | 0.2              | 0.68                    | 0.2              | 0.68                    |

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

Relative Humidity %

10-85%

Ambient Temperature

50-90 °F

/

10-32 °C

### PRODUCT SIZE

Depth

16.6 in.

42.3 cm

Width

17.9 in.

45.5 cm

Height

12.5 in.

31.8 cm

Weight

47.1 lbs

21.4 kg

### SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE

Class 1 Laser Product

Chemical Emission Test Method DE-UZ-219

The machine was tested under the conditions as specified in the standard inside a room of 2.41 m<sup>3</sup> with 1.0 air changes per hour.

### PARAMETER

TVOC

### Emission Rate

9.989 mg/h

Dust

0.31 mg/h

Ozone

< Limit of detection

Styrene

0.30 mg/h

Benzene

< Limit of detection



## Product Safety Data Sheet

Tested in accordance to ISO 7779 and declared per ISO 9296

|         | <b>Sound Power Level</b><br><b>LwAd (B)</b> | <b>Sound Pressure Level</b><br><b>Lpam (dBA)</b> |
|---------|---|--|
| Standby | 3.1   | 14   |
| Run     | 6.8   | 54   |

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Inquiries U.S. Only: 1-800-275-9376  
Contact U.S. Only: [askxerox@xerox.com](mailto:askxerox@xerox.com)  
Contact Non-U.S. Only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)