

Product Safety Data Sheet

SDS # : 24-00753 11-Sep-2024 Revision 2

AltaLink B8245

| Product Description | Multi-Function Equipment D-A501 / D-B501 |
|------------------------------|---|
| Speed (PPM) | 45 |
| Mono / Color | Monochrome |
| ELECTRICAL INPUT INFORMATION | |

| Voltage (Volts) | 110V-127V | 220V-240V |
|--------------------------|-----------|-----------|
| Rated Current (Amperes): | 12 | 8 |
| Frequency (Hertz) | 50/60 | 50/60 |
| Phase Connection | single | single |
| POWER AND HEAT | | |

| TEC Value (kWh/wk) | 0.64 | | 0.62 | |
|--|------------------|-------------------------|------------------|-------------------------|
| | Power (Watts) | Heat Output (BTU/Hr) | Power (Watts) | Heat Output (BTU/Hr) |
| Active ¹ | 713 | 2433 | 696 | 2374 |
| Ready ¹ | 66.3 | 226.2 | 66.3 | 226.2 |
| Sleep ¹ | 0.69 | 2.34 | 0.74 | 2.52 |
| Standby ¹ (Off/FEMP) ² | 0.02 | 0.08 | 0.06 | 0.2 |

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment.

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

| Relative Humidity % Ambient Temperature | 10-85% 50-90 °F / | 10-32 °C |
|--|---|--|
| PRODUCT SIZE Depth Width Height Weight | 28.5 in. 26.3 in. 45.1 in. 287 lbs | 72.3 cm 66.8 cm 114.7 cm 130 kg |

SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LED

LIGHT SOURCE:

Chemical Emission Test Methodology RAL - UZ205 The machine was tested under the conditions as specified in the standard inside a room of 2.0 m³ with 4.0 air changes per hour.

PARAMETER

| Total Volatile Organic Compounds (TVOC) | |
|---|--|
| Dust | |
| Ozone | |
| Styrene | |
| Benzene | |

Emission Rate 1.0 mg/h None detected None detected 0.03 mg/h 0.02 mg/h



Product Safety Data Sheet

Tested in accordance to ISO 7779 and declared per ISO 9296

Sound Power Level LwAd (dBA) 65.0 Sound Pressure Level

Run - continuous

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issaunce of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Inquiries U.S. Only: 1-800-275-9376 Contact U.S. Only: askxerox@xerox.com Contact Non-U.S. Only: ehs-europe@xerox.com