

0.62

## **Product Safety Data Sheet**

**SDS #**: 24-00753

2024-06-04 Revision 1

# AltaLink B8245

Product Description Multifunction Equipment D-A501 / D-B501

1E

Speed (PPM) 45

Mono / Color Monochrome

### **ELECTRICAL INPUT INFORMATION**

 Voltage (Volts)
 110V-127V
 220V-240V

 Rated Current (Amperes)
 12
 8

 Frequency (Hertz)
 50/60
 50/60

 Phase Connection
 single
 single

# POWER AND HEAT

| TEO value (KVVII/WK)                         | 0.04             |                         | 0.02             |                         |
|----------------------------------------------|------------------|-------------------------|------------------|-------------------------|
|                                              | Power<br>(Watts) | Heat Output<br>(BTU/Hr) | Power<br>(Watts) | Heat Output<br>(BTU/Hr) |
| Active <sup>1</sup>                          | ` 713 <i>`</i>   | ` 2433 ´                | ` 696 <i>´</i>   | 2374                    |
| Ready <sup>1</sup>                           | 66.3             | 226.2                   | 66.3             | 226.2                   |
| Sleep <sup>1</sup>                           | 0.69             | 2.34                    | 0.74             | 2.52                    |
| Standby <sup>1</sup> (Off/FEMP) <sup>2</sup> | 0.02             | 0.08                    | 0.06             | 0.2                     |

0.64

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### **OPERATING ENVIRONMENT**

Relative Humidity % 10-85% Ambient Temperature 50-90 °F / 10-32 °C

#### **PRODUCT SIZE**

 Depth
 28.5 in.
 72.3 cm

 Width
 26.3 in.
 66.8 cm

 Height
 45.1 in.
 114.7 cm

 Weight
 287 lbs
 130 kg

### SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

#### LIGHT SOURCE LED

Chemical Emission Test Method RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m³ with 4.0 air changes per hour.

 PARAMETER
 Emission Rate

 TVOC
 1.0 mg/h

 Dust
 None detected

 Ozone
 None detected

 Styrene
 0.03 mg/h

 Benzene
 0.02 mg/h

<sup>&</sup>lt;sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment

<sup>&</sup>lt;sup>2</sup> FEMP - Federal Energy Management Program



# **Product Safety Data Sheet**

Tested in accordance to ISO 7779 and declared per ISO 9296

Sound Power Level LwAd (B) 65.0

Run

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issaunce of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Inquiries U.S. Only: 1-800-275-9376 Contact U.S. Only: askxerox@xerox.com Contact Non-U.S. Only: ehs-europe@xerox.com