

Product Safety Data Sheet

SDS #: 24-00762

12-Nov-2024 Revision 1

Xerox® PrimeLink® C9275 Printer

Product Identifier Multi-Function Equipment J-A422/J-B421

Speed (PPM) 75 Mono / Color Colour

ELECTRICAL INPUT INFORMATION

 Voltage (Volts)
 110V-127V
 220V-240V

 Rated Current (Amperes):
 16
 10

 Frequency (Hertz)
 50/60
 50/60

 Phase Connection
 single
 single

POWER AND HEAT

TEC Value (kWh/wk) 1.40 1.41

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	1240	4230	1200	4090
Ready ¹	184	627	182	621
Sleep ¹	0.5	1.7	0.5	1.7
Standby ¹ (Off/FEMP) ²	0.2	0.7	0.2	0.7

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment.

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity % 15-85%

Ambient Temperature 50-82 °F / 10-28 °C

PRODUCT SIZE

 Depth
 31.2 in.
 79.3 cm

 Width
 63 in.
 166.0 cm

 Height
 45.4 in.
 115.4 cm

 Weight
 535 lbs
 242 kg

SPACE REQUIREMENTS Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE: LED

Chemical Emission Test Methodology DE-UZ-219

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m³ with 4.0 air changes per hour.

 PARAMETER
 Emission Rate

 Total Volatile Organic Compounds (TVOC)
 9 mg/h

 Dust
 None detected

 Ozone
 2.3 mg/h

 Styrene
 0.1 mg/h

 Benzene
 0.02 mg/h

² FEMP - Federal Energy Management Program



Product Safety Data Sheet

Tested in accordance to ISO 7779 and declared per ISO 9296

Sound Power Level LwAd (dBA)

Standby - Run - continuous 72.9

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issaunce of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Inquiries U.S. Only: 1-800-275-9376 Contact U.S. Only: askxerox@xerox.com Contact Non-U.S. Only: ehs-europe@xerox.com