

## **Product Safety Data Sheet**

**SDS #**: 20-00710

21-May-2025 Revision 6

# Xerox® Versant™280 Press

Product DescriptionPrinterSpeed (PPM)80Mono / ColorColor

#### **ELECTRICAL INPUT INFORMATION**

 Voltage (Volts)
 200V-240V

 Rated Current (Amperes)
 16-20A

 Frequency (Hertz)
 50/60

 Phase Connection
 single

#### **POWER AND HEAT**

TEC Value (kWh/wk)

| 120 value (KVIII III)                        | Power<br>(Watts) | Heat Output<br>(BTU/Hr) | Power<br>(Watts) | Heat Output<br>(BTU/Hr) |
|--|------------------|-------------------------|------------------|-------------------------|
| Active <sup>1</sup>                          | 1690             | 5770                    | (,               | , ,                     |
| Ready <sup>1</sup>                           | 435              | 1480                    |                  |                         |
| Sleep <sup>1</sup>                           | 154              | 525                     |                  |                         |
| Sleep (2) <sup>1</sup>                       | 1                | 3.4                     |                  |                         |
| Standby <sup>1</sup> (Off/FEMP) <sup>2</sup> | 0.04             | 0.1                     |                  |                         |

#### <sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

10-32 °C

#### **OPERATING ENVIRONMENT**

Relative Humidity % 15-85% Ambient Temperature 50-90 °F /

#### **PRODUCT SIZE**

 Depth
 33 in.
 83.1 cm

 Width
 30 in.
 76.0 cm

 Height
 48 in.
 121.2 cm

 Weight
 651 lbs
 295 kg

### SPACE REQUIREMENTS Refer to Installation Planning Guide

For additional information regarding different configurations please contact your local sales representative.

#### LIGHT SOURCE Class 1 Laser Product

Chemical Emission Test Method RAL - UZ205

The machine was tested under the conditions as specified in the standard inside a room of 5.1 m³ with 1 air changes per hour.

| PARAMETER | Emission Rate |
|-----------|---------------|
| TVOC      | 12 mg/h       |
| Dust      | 0.7 mg/h      |
| Ozone     | 1.9 mg/h      |
| Styrene   | 0.1 mg/h      |
| Benzene   | 0.06 mg/h     |



## **Product Safety Data Sheet**

Sound Power Level LwAd (B) Sound Pressure Level Lpam (dBA)

Standby - Run -

54.8 78.8

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issaunce of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Inquiries U.S. Only: 1-800-275-9376 Contact U.S. Only: askxerox@xerox.com Contact Non-U.S. Only: ehs-europe@xerox.com