

## Product Safety Data Sheet

SDS #: 26-00769

07-Jan-2026

Revision 1

# Xerox® Proficio® PX500 Production Press

### Product Description / Product Identifier

Production Press J-B501

Speed (PPM)

100

Mono / Color

Color

### ELECTRICAL INPUT INFORMATION

|                         | 208V   | 230V   |
|-------------------------|--------|--------|
| Voltage (Volts)         | 24     | 24     |
| Rated Current (Amperes) | 60     | 50     |
| Frequency (Hertz)       | single | single |

### POWER AND HEAT

PX300 Printer and optional EX server

|  | Power (Watts) | Heat Output (BTU/Hr) | Power (Watts) | Heat Output (BTU/Hr) |
|--|---------------|----------------------|---------------|----------------------|
| Active <sup>1</sup>                          | 2480          | 8450                 | 2320          | 7920                 |
| Ready <sup>1</sup>                           | 622           | 2120                 | 638           | 2180                 |
| Sleep <sup>1</sup>                           | 4.6           | 16                   | 4.2           | 14                   |
| Standby <sup>1</sup> (Off/FEMP) <sup>2</sup> | 0.2           | 0.7                  | 0.2           | 0.7                  |

<sup>1</sup> Power states defined per ENERGY STAR Program requirements for Imaging Equipment

<sup>2</sup> FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

### OPERATING ENVIRONMENT

|                     |                     |
|---------------------|---------------------|
| Relative Humidity % | 15-85%              |
| Ambient Temperature | 50-82 °F / 10-28 °C |

### PRODUCT SIZE

|        |          |          |
|--------|----------|----------|
| Depth  | 32.8 in. | 83.3 cm  |
| Width  | 105 in.  | 267 cm   |
| Height | 53.9 in. | 137.0 cm |
| Weight | 1585 lbs | 719 kg   |

### SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

### LIGHT SOURCE

LED

Chemical Emission Test Method DE-UZ-219

The machine was tested under the conditions as specified in the standard inside a room of 2.0 m<sup>3</sup> with 4.0 air changes per hour.

### PARAMETER

| PARAMETER | Emission Rate |
|-----------|---------------|
| TVOC      | 15 mg/h       |
| Dust      | None detected |
| Ozone     | 4.8 mg/h      |
| Styrene   | 0.1 mg/h      |
| Benzene   | 0.03 mg/h     |



## Product Safety Data Sheet

Tested in accordance to ISO 7779 and declared per ISO 9296

|         | <b>LwAd (dBA)</b> |
|---------|-------------------|
| Standby | 56.9              |
| Run     | 81.1              |

Xerox Corporation has developed this Product Safety Data sheet for informational purposes as a courtesy for Xerox customers. Any determination regarding the proper use of this information must be made by the user, including any use of the information for compliance with applicable laws, rules and regulations. Xerox believes the information herein to be accurate as of the date of issuance but makes no representations or warranties of any kind, either express or implied, as to the accuracy, completeness or fitness for use of the information. By issuance of this Product Safety Data Sheet, Xerox does not assume any liability or responsibility for losses, claims, liabilities or damages which may result from reliance upon the information herein.

Inquiries U.S. Only: 1-800-275-9376  
Contact U.S. Only: [askxerox@xerox.com](mailto:askxerox@xerox.com)  
Contact Non-U.S. Only: [ehs-europe@xerox.com](mailto:ehs-europe@xerox.com)